

January 10, 2001

Ms. Lisha Cordova State of Utah Division of Oil, Gas & Mining 1594 West North Temple, Suite 1210 Salt Lake City, UT 84114

RE: APD'S

Dear Ms. Cordova:

Enclosed are copy's of the Application's for Permit to Drill, for the following wells listed below:

NBU #315 SE/NE Sec.11, T9S, R21E NW/SE Sec.15, T9S, R21E

FEDERAL #35-179 SW/NE Sec. 35, T8S, R21E

If you have any questions or need additional information on the above referenced APD's please contact me at (435) 781-7023.

Sincerely,

Cheryl Cameron

Sr. Regulatory Analyst

DA: Enclosure

Form 316<sup>A</sup>·3 (August 1999)

# UNITED STATES DEPARTMEN THE INTERIOR BUREAU OF LAZD MANAGEMENT


FORM APPROVED OMB NO. 1004-0136 Expires: November 30, 2000

			5.	Lease Serial No.		
APPLICATION FOR PERMIT TO D	RILL OR	REENTER		U-0141317		
la. Type of Work X DRILL R	EENTER		6.	If Indian, Allotee or	Tribe Name	
			<u></u>	<u> Uintah &amp; Oura</u>	У	
1b. Type of Well Oil Well X Gas Well Other		Single Zone Multiple Zone	7.	7. Unit or CA Agreement Name and No.		
				Natural Butte		
2. Name of Operator			8.	Lease Name and We	II No.	
Coastal Oil & Gas Corporation  3a. Address		3b. Phone No. (include area coo	le)	NBU #315 API Well No.		
		(435) -781-7023	9.	N/A 43-04	7-33879	
P.O. Box 1148, Vernal, UT 84078 4. Location of Well (Report location clearly and in accordance with	any State eq	uirements)*	10	Field and Pool, or Ex		
A 4		4434476 N 626955 E	- 1	Natural Butte	8	
At surface SE NE		1.21.955 F	11	Sec., T., R., M., or F	3lk. and Survey or Are	
At proposed prod. zone 1798 FNL & 770 FEL		020 195 2		Section 11-T9	S-R21E	
14. Distance in miles and direction from nearest town or post office*		4	12	County or Parish	13. State	
19.9 Miles Northwest	t of Our	av. IItah	U	intah	Utah	
15. Distance from proposed*		5. No. of Acres in lease		ng Unit dedicated to	this well	
location to nearest				_		
property or lease line, ft. 770		480		N/A		
(Also to nearest drg. unit line, if any)			20 7/1	(DYA D. 131		
18. Distance from proposed location*	1	9. Proposed Depth	20.BLM	I/BIA Bond No. on f	ne	
to nearest well, drilling, completed, applied for, on this lease, ft.						
Refer to Topo	'C"	7400'		บ-60538	2-9	
21. Elevations (Show whether DF, KDB, RT, GL, etc.	1	22. Approximate date work will sta	rt*	23. Estimated dura	ation	
4849.2'Ungraded GL		Upon Approval			To Be Determined	
	24	Attachments				
The following, completed in accordance with the requirements of On	shore Oil an	d Gas Order No. 1, shall be attache	ed to this	form:		
and the second of the second o		4. Bond to cover the operat	ions unles	s covered by an exist	ing bond on file (see	
<ol> <li>Well plat certified by a registered surveyor.</li> <li>A Drilling Plan</li> </ol>		Item 20 above).				
3. A Surface Use Plan (if the location is on National Forest System	Lands, the	the 5. Operator certification.				
SUPO shall be filed with the appropriate Forest Service Office).		6. Such other site specific i	nformatio	n and/or plans as may	y be required by the	
		authorized officer.				
25. Signuature	Nan	ne (Printed/Typed)		Date		
	Ch	eryl Cameron (	a n a	TE EV	1/8/01	
- Tury Elmun			1 1	5 1111		
Title	•	, , ,	. 27			
Sr. Regulatory Analyst	<u> </u>	100	7 7	Date		
Approved by (Signautre)	Nar Nar	ne (Printed/Typed) JAN BRADLEY G.		Date	1-29-01	
Drodler Wx		- DECLARATION OF			1 21 01	
Application approval does not warrant or certify that the applicant	Off	DIV OF CO.	(C. 13)	MINIFIG		
Application approval does not warrant or certify that the applicant	holds legal o	or equitable title to those rights in	the subie	ct lease which would	1 entitle the applicant	
conduct operations thereon.	iobai v	·			••	
Conditions of approval, if any, are attached.						

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowlingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## T9S, R21E, S.L.B.&M.

Uintah County Alum. Сар оп 5/8" Rebar, Pile of Stones



## LEGEND:

\_\_ = 90° SYMBOL

= PROPOSED WELL HEAD.


= SECTION CORNERS LOCATED.

## COASTAL OIL & GAS CORP.

Well location, NBU #315, located as shown in the SE 1/4 NE 1/4 of Section 11, T9S, R21E, S.L.B.&M., Uintah County, Utah.

## BASIS OF ELEVATION

SPOT ELEVATION AT THE NORTH 1/4 CORNER OF SECTION 11, T9S, R21E, S.L.B.&M. TAKEN FROM THE OURAY SE QUADRANGLE, UTAH, UINTAH COUNTY, 7.5 MINUTE SERIES (TOPOGRAPHICAL MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 4857 FEET.



#### CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME DIS LINDER BY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF

REGISTERED EAND SURVEYOR REGISTRATION NO KYATE 19 STATE OF UTAH

## UINTAH ENGINEERING & LANDISHRYEYING 85 SOUTH 200 EAST - VERNAL, UTAH 84078

(435) 789-1017

SCALE 1" = 1000'		DATE SURVEYED: DATE DRAWN: 10-15-98 11-04-98		
PARTY D.A. C.G.	D.R.B.	REFERENCES G.L.O. PLA	ΑT	
WEATHER WARM		FILE COASTAL OIL	& GAS CORP.	

## COASTAL OIL & GAS CORP.

## NBU #315 SECTION 11, T9S, R21E, S.L.B.&M.

PROCEED IN A WESTERLY DIRECTION FROM VERNAL, UTAH ALONG U.S. HIGHWAY 40 APPROXIMATELY 14.0 MILES TO THE JUNCTION OF STATE EXIT LEFT AND PROCEED IN A SOUTHERLY DIRECTION HIGHWAY 88: APPROXIMATELY 17.0 MILES TO OURAY, UTAH; PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 6.9 MILES ON THE SEEP RIDGE ROAD TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE EAST; TURN LEFT AND PROCEED IN AN EASTERLY DIRECTION APPROXIMATELY 5.0 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTH: TURN LEFT AND PROCEED IN A NORTHERLY DIRECTION APPROXIMATELY 0.3 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTHEAST; TURN RIGHT AND PROCEED IN A NORTHEASTERLY DIRECTION APPROXIMATELY 5.5 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTHWEST; TURN LEFT AND PROCEED IN A NORTHWESTERLY DIRECTION APPROXIMATELY 0.6 MILES, TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE WEST; TURN LEFT AND PROCEED IN A WESTERLY, THEN NORTHWESTERLY DIRECTION APPROXIMATELY 1.8 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTH; TURN RIGHT AND PROCEED IN A NORTHERLY DIRECTION APPROXIMATELY 0.4 MILES TO THE PROPOSED LOCATION.

TOTAL DISTANCE TO VERNAL IS APPROXIMATELY 51.2 MILES.

## NBU #315 SE/NE Sec. 11-T9S-R21E UINTAH COUNTY, UTAH U-0141317

## ONSHORE ORDER NO. 1 COASTAL OIL & GAS CORPORATION

## DRILLING PROGRAM

## 1. Estimated Tops of Important Geologic Markers:

	300'
Green River	350'
Wasatch 52	275'
TD 69	900'

## 2. Estimated Depths of Anticipated Water, Oil, Gas, or Mineral Formations:

Substance	<u>Formation</u>	<u>Depth</u>
	Green River	1850'
Gas	Wasatch	5275'
Water	N/A	
Other Minerals	N/A	

## 3. Pressure Control Equipment (Schematic Attached)

Please see the Natural Buttes Unit Standard Operating Procedure (SOP).

## 4. Proposed Casing & Cementing Program:

Please see the Natural Buttes Unit SOP.

## 5. Drilling Fluids Program:

Please see the Natural Buttes Unit SOP.

## 6. Evaluation Program:

Please see the Natural Buttes Unit SOP.

## 7. Abnormal Conditions:

Maximum anticipated bottomhole pressure calculated at 6900' TD, approximately equals 2,760 psi (calculated at 0.4 psi/foot).

Maximum anticipated surface pressure equals approximately 1,242 psi (bottomhole pressure minus the pressure of a partially evacuated hole calculated at 0.22 psi/foot).

## NBU #315 SE/NE Sec. 11-T9S-R21E UINTAH COUNTY, UTAH U-0141317

## ONSHORE ORDER NO. 1

## MULTI-POINT SURFACE USE & OPERATIONS PLAN

An onsite inspection was conducted for the NBU #315 on 1/3/01, for the subject well.

## 1. Existing Roads:

The proposed well site is approximately 19.9 miles northwest of Ouray, Utah. Directions to the location from Ouray, Utah:

Proceed in a westerly direction from Vernal, Utah, along U.S. Highway 40 approximately 14.0 miles to the junction of state highway 88; exit left and proceed in a southerly direction approximately 17.0 miles to Ouray, Utah; proceed in a southerly direction approximately 6.9 miles on the Seep Ridge Road to the junction of this road and an existing road to the east; turn left and proceed in an easterly direction approximately 5.0 miles to the junction of this road and an existing road to the north; turn left and proceed in a northerly direction approximately 0.3 miles to the junction of this road and an existing road to the northeast; turn right and proceed in a northeasterly direction approximately 5.5 miles the junction of this road and an existing road to the northwest; turn left and proceed in a northwesterly direction approximately 0.6 miles to the junction of this road and an existing road to the west; turn left and proceed in a westerly, then northwesterly direction approximately 1.8 miles to the junction of this road and an existing road to the north; turn right and proceed in a northerly direction approximately 0.4 miles to the proposed location.

Refer to Topo Maps A and B for location of access roads within a 2-mile radius.

## 2. Planned Access Roads:

Please see the Natural Buttes Unit Standard Operating Procedure (SOP).

Refer to Topo Map B for the location of the propose access road.

## 3. Location of Existing Wells Within a 1-Mile Radius:

Please refer to Topo Map C.

## 4. Location of Existing & Proposed Facilities:

Please see the Natural Buttes Unit SOP.

Refer to Topo Map D for the location of the proposed pipeline.

## 5. Location and Type of Water Supply:

Please see the Natural Buttes SOP.

## 6. Source of Construction Materials:

Please see the Natural Buttes SOP.

## 7. <u>Methods of Handling Waste Materials</u>:

Please see the Natural Buttes SOP.

Any produced water from the proposed well will be contained in a water tank and will then be hauled by truck to one of the pre-approved disposal sites: RNI, Sec.5,T9S,R22E, NBU #159, Sec.35,T9S,R21E, Ace Oilfield Sec.2, T6S,R20E, MC&MC Sec 12, T6S,R19E (Requests is lieu of filing Form 3160-5, after initial production).

## 8. Ancillary Facilities:

Please see the Natural Buttes SOP.

## 9. Well Site Layout: (See Location Layout Diagram)

The attached Location Layout Diagram describes drill pad cross-sections, cuts and fills, and locations of the mud tanks, reserve pit, flare pit, pipe racks, trailer parking, spoil dirt stockpile(s), and surface material stockpile(s).

Please see the attached diagram to describe rig orientation, parking areas, and access roads.

As per previous onsite discussions, a reserve pit liner (12 Mil) will be required.

## 10. Plans for Reclamation of the Surface:

Please see the Natural Buttes SOP.

## 11. Surface Ownership:

The well pad and access road are located on lands owned by:

Bureau of Indian Affairs Uintah & Ouray Agency P.O. Box 130 Fort Duchesne, UT 84026 (435)722-4300

## 12. Other Information:

A Class III archaeological survey was conducted by Metcalf Archaeological Consultants. A copy of this report is attached.

This location is not within 460 feet from the boundary of the Natural Buttes Unit, nor is it within 460 feet of any non-committed tract lying within the boundaries of the Unit.

## 13. Lessee's or Operators's Representative & Certification:

Cheryl Cameron Sr. Regulatory Analyst Coastal Oil & Gas Corporation P.O. Box 1148 Vernal, UT 84078 (435) 781-7023 Darrell Molnar
Drilling Manager
Coastal Oil & Gas Corporation
9 Greenway Plaza, Suite 2770
Houston, TX 77046
(713) 418-4295

Certification: All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved Plan of Operations, and any applicable Notice to Lessees.


Coastal Oil & Gas Corporation is considered to be the operator of the subject well. Coastal Oil & Gas Corporation agrees to be responsible under the terms and conditions of the lease for the operations conducted upon leased lands.


Bond Coverage pursuant to 43 CFR 3104 for lease activities is being provided by Coastal Oil & Gas Corporation Bond #102103, BLM Nationwide Bond #U-605382-9, and BIA Nationwide Bond #114066-A.

The Operator will be fully responsible for the actions of its subcontractors. A complete copy of the approved "Application for Permit to Drill" will be furnished to the field representative(s) to ensure compliance and shall be on location during all construction and drilling operations.


I hereby certify that I, or persons under my supervision, have inspected the proposed drill site and access route, that I am familiar with the conditions that currently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and the work associated with the operations proposed herein will be performed by the Operator, its contractors, and subcontractors in conformity with this plan and the terms and conditions under which it is approved.


Chely Camun	1//8/01
Cheryl Cameron	Date















## COASTAL OIL & GAS CORPORATION

## **DRILLING PROGRAM**

DATE 9/5/00 Coastal Oil & Gas Corporation **COMPANY NAME NBU #315** TD 7,400' MD/TVD **WELL NAME** KB ELEVATION 4,800' **COUNTY Uintah** STATE Utah **FIELD** NBU Straight Hole BHL SURFACE LOCATION 1798' FNL & 770' FEL, Section 11 T9S-R21E OBJECTIVE ZONE(S) Wasatch



# COASTAL OIL & GAS CORPORATION DRILLING PROGRAM

## **CASING PROGRAM**

						DESIGN FACTORS		JKS
	SIZE	INTERVAL	WT.	GR.	CPLG.	BURST	COLLAPSE	TENSION
CONDUCTOR	14"	0-40'					1	
						2950	1370	263000
SURFACE	8-5/8"	0-250'	24#	K-55	STC	21.03	11.71	4.70
<del> </del>						5350	4960	180000
PRODUCTION*	4-1/2"	0-TD	11.6#	K-55	LTC	2.05	1.29	1.33

- 1) Maximum Anticipated Surface Pressure (MASP) (Conductor and Surface Casings) = (Frac Gradient at Shoe Gas Gradient (0.115 psi/ft))(TVD)
- 2) MASP (Int Casing) = Pore Pressure at Next Casing Point (Gas Gradient x TVD of Next Casing Point x 0.67) (Mud Weight x TVD x 0.052 x 0.33)
- 3) MASP (Prod Casing) = Pore Pressure (Gas Gradient x TVD of Production Interval)

(Burst Assumptions: FG @ 8-5/8" shoe = 13.0 ppg, Max Pore Pressure = 9.0 ppg EMW)

(Collapse Assumption: Fully Evacuated Casing, Max MW)

(Tension Assumptions: Air Weight of Casing, 50,000 lbs overpull)

## **CEMENT PROGRAM**


		FT. OF FILL	DESCRIPTION	SACKS	EXCESS*	WEIGHT	YIELD
SURFACE		250	Class G + 2% CaCl <sub>2</sub> + 0.25 lb/sk Cello	90	35%	15.80	1.17
	1		Flake				
PRODUCTION	LEAD	4975	Premium Lite II + 3 lb/sk CSE	650	100%	11.00	3.44
			+ 0.5% Sodium Metasilicate				
			+ 10% Gel + 0.25 lb/sk Cello Flake				
			+ 3% Salt + 3 lb/sk Kol Seal				
	TAIL	2425	50/50 POZ + 0.1% R-3 + 1% EC-1	790	75%	14.5	1.23
			+ 0.2% Sodium Metasilicate				
			+ 2% Gel + 0.5% FL-25				
			+ 3% Salt				

<sup>\*</sup> or 15% over caliper log

## **FLOAT EQUIPMENT & CENTRALIZERS**

SURFACE	Guide shoe, 1 jt, float collar. Centralize first 3 joints & every other joint to surface with bow spring centralizers. Thread lock FE up to & including pin end of FC.
PRODUCTION	Guide shoe, 1 jt, float collar. Centralize first 3 joints & every other joint to top of tail cement with bow spring centralizers.

## WELLHEAD EQUIPMENT



# COASTAL OIL & GAS CORPORATION DRILLING PROGRAM

## BIT PRO

NTERVAL   NOLE   SIT MFG & MODEL   GPM   SERIAL   NZLS   COMMENTS			ROCK BIT & PDC			NZLS	COMMENTS
Surf Csg - TD 7-7/8" SEC XS44 Au/Mist New 16-16-16  Surf Csg - TD 7-7/8" SEC XS44 Au/Mist New 16-16-16  Aerated  If an additional bit is required use another insert.  If an additional bit is required use another insert.  Depth Log Type Platform Express  SC - TD Platform Express  MUD LOGGER: SC - TD Platform Express  SAMPLES: As per Geology CORING: NA DST: NA  PEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT  O-Trona Air/Mist NA NA Polymer, Gal Gyp, Lime  Trone-TD Aerated Water NA NC NA Polymer, Gal Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out. BOPE: 11" 3M with one annular and 2 pams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. BOPE: 11" 3M with one annular and 2 pams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. BOPE: 11" 3M with one annular and 2 pams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Run Totos survey every 1,500 from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees. Treat for corrosion as per plan.  DATE:				GPM	SERIAL	NZLS	COMMENTS
If an additional bit is required use another insert.    If an additional bit is required use another insert.	Surface Hole	11"	various				
If an additional bit is required use another insert.    If an additional bit is required use another insert.	Surf Cog. TD	7_7/8"	SEC XS44	Air/Mist	New	16-16-16	
Depth Log Type  SC - TD Platform Express  MUD LOGGER: SC - TD  SAMPLES: As per Geology CORING: NA DST: NA  DST: NA  DEPTH TYPE NUD WT LOSS VISCOSITY TREATMENT O-Trona Air/Mist NA NA Gyp, Lime  (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gel Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out. Record on chart recorder 8 tour sheet. Function test rems on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totos survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.	Suit Csg - TD	1-110	0207.011				
Depth Log Type  SC - TD Platform Express  MUD LOGGER: SC - TD  SAMPLES: As per Geology CORING: NA DST: NA  DST: NA  DEPTH TYPE NUD WT LOSS VISCOSITY TREATMENT O-Trona Air/Mist NA NA Gyp, Lime  (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gel Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out. Record on chart recorder 8 tour sheet. Function test rems on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totos survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.							
Depth Log Type  SC - TD Platform Express  MUD LOGGER: SC - TD  SAMPLES: As per Geology CORING: NA DST: NA  DST: NA  DEPTH TYPE NUD WT LOSS VISCOSITY TREATMENT O-Trona Air/Mist NA NA Gyp, Lime  (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gel Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out. Record on chart recorder 8 tour sheet. Function test rems on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totos survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.							
Depth							
Depth Log Type  SC - TD Platform Express  MUD LOGGER: SC - TD  SAMPLES: As per Geology CORING: NA DST: NA  DST: NA  DEPTH TYPE NUD WT LOSS VISCOSITY TREATMENT O-Trona Air/Mist NA NA Gyp, Lime  (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gel Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out. Record on chart recorder 8 tour sheet. Function test rems on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totos survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.	If an additional bit is	required use another	er insert.		,		
Dapth Log Type SC - TD Platform Express  MUD LOGGER: SC - TD SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM     Depth Type MUD WT Loss VISCOSITY TREATMENT Polymer, Gel Gyp, Lime							
Depth Log Type SC - TD Platform Express  MUD LOGGER: SC - TD SAMPLES: As per Geology CORING: NA DST: NA  DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT 0-Trona Air/Mist NA NA Polymer, Gel (0 - +/-2,000')  Trona-TD Aerated Water NA NC NA Polymer, Gel (+/-2,000' - TD)  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psl after installing. Test surface casing to 1,500 psl prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totoo survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.							
Depth SC - TD Platform Express  MUD LOGGER: SC - TD SAMPLES: As per Geology CORING: NA DST: NA  DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT 0-Trona Air/Mist NA NA Polymer, Gel (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gel (y-/-2,000' - TD) Aerated Water NA NC NA Polymer, Gel (+/-2,000' - TD) Aerated Water NA NC NA Polymer, Gel (-/-2,000' - TD)	SICAL DATA						
Depth SC - TD Platform Express  MUD LOGGER: SC - TD SAMPLES: As per Geology CORING: NA DST: NA  DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT 0-Trona Air/Mist NA NA Polymer, Gel (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gel (y-/-2,000' - TD) Aerated Water NA NC NA Polymer, Gel (+/-2,000' - TD) Aerated Water NA NC NA Polymer, Gel (-/-2,000' - TD)							
MUD LOGGER: SC - TD SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM    DEPTH	LOGGING:						
MUD LOGGER: SC - TD SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM    DEPTH	-	Denth			Log T	ype	
MUD LOGGER: SC - TD  SAMPLES: As per Geology CORING: NA  DST: NA  PROGRAM     DEPTH							
SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM    DEPTH		00 15					
SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM    DEPTH							
SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM    DEPTH							
SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM    DEPTH							
SAMPLES: As per Geology CORING: NA DST: NA  PROGRAM    DEPTH		ec to					
CORING: NA  DST: NA  NA  PROGRAM    NA			ogy				
DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT  O-Trona Air/Mist NA NA Polymer, Gel  (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gyp, Lime  Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.			-9/				
DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT  0-Trona Air/Mist NA NA NA Polymer, Gel (0 - +/-2,000') Aerated Water NA NC NA Polymer, Gyp, Lime  Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.							
DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT  0-Trona Air/Mist NA NA NA Polymer, Gel (0 - +/-2,000')  Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  (+/-2,000' - TD)  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.	DST:	NA					
DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT  0-Trona Air/Mist NA NA NA Polymer, Gel (0 - +/-2,000')  Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder 8 tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DST:	NA					
DEPTH TYPE MUD WT LOSS VISCOSITY TREATMENT  0-Trona Air/Mist NA NA NA Polymer, Gel (0 - +/-2,000')  Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder 8 tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:		<u>NA</u>					
O-Trona Air/Mist NA NA NA Polymer, Gel Gyp, Lime  Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11* 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder 8 tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.		NA	W	TED			
Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.	ROGRAM				viscosit)	·	TREATMENT
Trona-TD Aerated Water NA NC NA Polymer, Gyp, Lime  (+/- 2,000' - TD)  Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.	ROGRAM DEPTH	ТҮРЕ	MUD WT L	oss V	VISCOSITY	, <u> </u>	
Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder 8 tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona	ТҮРЕ	MUD WT L	oss V	VISCOSITY	<i>y</i>	Polymer, Gel
Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder 8 tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona	ТҮРЕ	MUD WT L	oss V	VISCOSITY	/	Polymer, Gel
Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona	ТҮРЕ	MUD WT L	oss V	VISCOSITY		Polymer, Gel Gyp, Lime
Circulate hole until clean @ TD. Spot brine pill at TD for logs and casing.  TIONAL INFORMATION  Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.	DEPTH 0-Trona (0 - +/-2,000')	TYPE Air/Mist	MUD WT LO	NA A			Polymer, Gel Gyp, Lime
Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')	TYPE Air/Mist	MUD WT LO	NA A			Polymer, Gel Gyp, Lime
Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.	DEPTH 0-Trona (0 - +/-2,000')	TYPE Air/Mist	MUD WT LO	NA A			Polymer, Gel Gyp, Lime
Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)	Aerated Water	MUD WT LO	DSS NA NC	NA		Polymer, Gel Gyp, Lime
Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)	Aerated Water	MUD WT LO	DSS NA NC	NA		Polymer, Gel Gyp, Lime
Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.  BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder & tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)	Aerated Water	MUD WT LO	DSS NA NC	NA		Polymer, Gel Gyp, Lime
BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder to tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until	Air/Mist  Aerated Water	MUD WT LO	DSS NA NC	NA		Polymer, Gel Gyp, Lime
BOPE: 11" 3M with one annular and 2 rams. Test to 3,000 psi (annular to 1,500 psi) prior to drilling out. Record on chart recorder to tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until	Air/Mist  Aerated Water	MUD WT LO	DSS NA NC	NA		Polymer, Gel Gyp, Lime
tour sheet. Function test rams on each trip. Maintain safety valve & inside BOP on rig floor at all times. Kelly to be equipped with up & lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until	Air/Mist  Aerated Water  clean @ TD. Spot	NA NA NA Drine pill at TD for logs	NC and casing	NA g.		Polymer, Gel Gyp, Lime
& lower kelly valves.  Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until	Air/Mist  Aerated Water  I clean @ TD. Spot	NA  NA  NA  brine pill at TD for logs  Test surface casing to	NC and casing	NA g. r to drilling o	out.	Polymer, Gel Gyp, Lime  Polymer, Gyp, Lime
Run Totco survey every 1,500' from surface casing shoe to TD. Maximum allowable hole angle is 5 degrees.  Treat for corrosion as per plan.  JECT ENGINEER:  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until	Aerated Water  Aerated Water  Clean @ TD. Spot	NA  NA  NA  brine pill at TD for logs  Test surface casing to ans. Test to 3,000 psi (and	,500 psi prio	NA g. r to drilling o	out.	Polymer, Gel Gyp, Lime  Polymer, Gyp, Lime  ecord on chart recorder &
Treat for corrosion as per plan.  JECT ENGINEER:  DATE:	DEPTH 0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until  CINCLINFORMATION  Test casing head to BOPE: 11" 3M with a tour sheet. Function	Aerated Water  Aerated Water  Clean @ TD. Spot  750 psi after installing one annular and 2 ran test rams on each trig	NA  NA  NA  brine pill at TD for logs  Test surface casing to ans. Test to 3,000 psi (and	,500 psi prio	NA g. r to drilling o	out.	Polymer, Gel Gyp, Lime  Polymer, Gyp, Lime  ecord on chart recorder &
JECT ENGINEER: DATE:	DEPTH  0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until  CINCLINFORMATION  Test casing head to BOPE: 11" 3M with a tour sheet. Function & lower kelly valves.	Aerated Water  Aerated Water  Clean @ TD. Spot  T50 psi after installing one annular and 2 rand test rams on each trip	NA  NA  NA  NA  NA  Test surface casing to ans. Test to 3,000 psi (and p. Maintain safety valve 8)	,500 psi prio	NA  g. r to drilling of psi) prior to on rig floor a	out. o drilling out. Re at all times. Kell	Polymer, Gel Gyp, Lime  Polymer, Gyp, Lime  ecord on chart recorder &
JECT ENGINEER:	DEPTH  0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until  Circulate hole until  BOPE: 11" 3M with a tour sheet. Function & lower kelly valves. Run Totco survey even	Air/Mist  Aerated Water  Aerated Water  Clean @ TD. Spot  750 psi after installing one annular and 2 ran test rams on each trip	NA  NA  NA  NA  NA  Test surface casing to ans. Test to 3,000 psi (and p. Maintain safety valve 8)	,500 psi prio	NA  g. r to drilling of psi) prior to on rig floor a	out. o drilling out. Re at all times. Kell	Polymer, Gel Gyp, Lime  Polymer, Gyp, Lime  ecord on chart recorder &
JECT ENGINEER:	DEPTH  0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until  Circulate hole until  BOPE: 11" 3M with a tour sheet. Function & lower kelly valves. Run Totco survey even	Air/Mist  Aerated Water  Aerated Water  Clean @ TD. Spot  750 psi after installing one annular and 2 ran test rams on each trip	NA  NA  NA  NA  NA  Test surface casing to ans. Test to 3,000 psi (and p. Maintain safety valve 8)	,500 psi prio	NA  g. r to drilling of psi) prior to on rig floor a	out. o drilling out. Re at all times. Kell	Polymer, Gel Gyp, Lime  Polymer, Gyp, Lime  ecord on chart recorder &
I FILIPERA TILL	DEPTH  0-Trona (0 - +/-2,000')  Trona-TD (+/- 2,000' - TD)  Circulate hole until  IONAL INFORMATION  Test casing head to BOPE: 11" 3M with tour sheet. Function & lower kelly valves.  Run Totco survey every reaction of the corresion of the corresion.	Air/Mist  Aerated Water  Aerated Water  Clean @ TD. Spot  750 psi after installing one annular and 2 ran test rams on each trip	NA  NA  NA  NA  NA  Test surface casing to ans. Test to 3,000 psi (and p. Maintain safety valve 8)	,500 psi prio	NA  g. r to drilling of psi) prior to on rig floor a	out. o drilling out. Re at all times. Kell	Polymer, Gel Gyp, Lime  Polymer, Gyp, Lime  ecord on chart recorder &

Darrell Molnar



January 19, 1999

DENVER DISTRICT - E & S

Ms. Sheila Bremer Coastal Oil & Gas Corp. P. O. Box 749 Denver, CO 80201-0749

XC: Orly RJL PEB

Dear Ms. Bremer:

Enclosed is a Metcalf Archaeological Consultants, Inc. (MAC) cultural resource inventory report covering ten Coastal Oil & Gas well projects in Uintah County, Utah. Well pad projects CIGE #237, CIGE #238, NBU #314, and NBU #315 are on land owned and controlled by the Ute Indian Tribe, Uintah and Ouray Agency of Fort Duchesne, Utah, and well pad projects NBU #322, NBU #324, NBU #325, NBU #334, NBU #343, and NBU #346 are on land administered by the BLM.

Ute well projects NBU #314 and NBU #315 involved no cultural resources and cultural clearance is recommended for these two projects. On the CIGE #237 project a new prehistoric site with the potential for significant deposits was recorded (42UN2600), a small portion of previously recorded site 42UN2035 was encountered, and three isolates were discovered on the associated pipeline. The well pad centerstake for CIGE #237 was moved 50 feet southwest to a recommended location. Moving the pad to the new location and limiting its construction to staked boundaries will effectively avoid any significant portions of 42UN2600. 42UN2035 will not be impacted by construction of CIGE #237. It is additionally recommended that construction of the CIGE #237 well pad be monitored by Ute Tribal Representative Mr. Ignacio. Monitoring is to insure that construction is confined to staked limits. An isolate by definition is not significant and no further work is needed for the three recorded on the proposed pipeline for CIGE #237. The proposed location and access for CIGE #238 was partially staked in previously recorded site 42UN2143, which appears significant and potentially eligible for the National Register. The centerstake was moved 260 feet northwest to a recommended location. This action effectively moved the well pad's APE outside of the site boundaries. In addition to moving the well, the access road was reconfigured further to the north to accommodate the pad's new location and will avoid the site. Although no cultural resources were observed in the

proceed had's new location, it is still close to a known site and in sandy denosition, and because

also recommended that the pad's construction be monitored by a qualified archaeologist and Ute Tribal Representative to inspect for any new deposits that might be uncovered by construction and to insure that construction does not exceed its staked limits. Cultural resource clearance is recommended for CIGE #237 and CIGE #238 with the above stipulations and with approval from the Uintah and Ouray Cultural Rights and Protection Department.

Five of the cultural resource inventories on the BLM land were negative, resulting in no cultural material being recorded. Near the access corridor of the sixth project (NBU #323) one historical site was recorded. This site, 42UN2599, is not significant and not recommended to be eligible for listing on the National Register. Cultural resource clearance is recommended for all six of the BLM well pad projects.

If you have any questions or need further assistance do not hesitate to contact us.

Sincerely,

John M. Scott Staff Archaeologist

She M. Sate

Enclosure

cc: Blaine Philips, BLM Vernal District, Vernal UT

Betsie Chapoose, Cultural Rights and Protection, UIT, Ft. Duchesne, UT

Ferron Secakuku, Energy and Minerals, UIT, Ft. Duchesne, UT Dale Hanberg, Bureau of Indian Affairs, Ft. Duchesne, UT

Amy Huslein, Bureau of Indian Affairs, Phoenix, AZ

# Coastal Oil & Gas Company: Ten Class III Cultural Resource Inventories on Ute & BLM Land, Uintah County, Utah

prepared by
John M. Scott
Metcalf Archaeological Consultants, Inc.
P.O. Box 899
Eagle, CO 81631

prepared for Coastal Oil & Gas Company Denver, CO

Bureau of Land Management Cultural Resources Permit # 98-UT-54945 expires May 1, 1999

Project No. U-99-MM-0002b,i

January 1999

## Introduction

Metcalf Archaeological Consultants, Inc. (MAC) conducted 10 Class III cultural resource inventories for Coastal oil and Gas Corporation of Denver, Colorado. The inventories were for well pad projects in Uintah County, Utah and include associated roads and pipelines. Four of the inventories were on Ute Tribal land and six were on land administered by the Bureau of Land Management (BLM). The projects are listed in Table 1, which shows legal locations, staked footage, and total acreage inventoried. It also shows the direction and length of the access roads and pipelines that were inventoried.

Table 1 Well Locations and Accompanying Information

	* 1.TO /C	France	Access Dist/Dir2	Pipeline Dis¹/Dir¹	Acres
Ute Wells	Legal T/R/S	Footage	250ft NW	1450ft NW&E	13.9
CIGE #237	9S/21E/15	1634FSL 2127FEL	25011 IN W	145011 1 W &L	13.7
CIGE #238	9S/21E/20	819FSL 592FEL	1027ft W	492ft NW&NE	13.5
NBU #314	9S/21E/11	706FNL 857FEL	in 10-acre block	in 10-acre block	10
NBU #315	9S/21E/11	1798FNL 770FEL	in 10-acre block	in 10-acre block	10
			Total Acres for U	Jte Wells	<u>47.4</u>
BLM Wells					
22212 11 11 11	9S/22E/30	991FNL 444FEL	200ft W	500ft S	11.6
NBU #323	93/222/30	9911 NE 4441 DE			
NBU #324	9S/22E/30	1826FSL 1147FEL	2100ft NW	400ft S	15.8
NBU #325	9S/22E/30	403FSL 1694FEL	400ft N	in 10-acre block	11
NBU #334	10S/22E/3	2179FSL 272FEL	in 10-acre block	1660 S	13.8
NBU #343	10S/22E/08	903FNL 1754FWL	1224ft S	400ft S	13.9
NBU #346	10S/22E/10	811FSL 1138FEL	in 10-acre block	3200ft N	17.3
			Total Acres for	BLM Wells	83.4
			Total Acres All	Wells	130.8

<sup>&</sup>lt;sup>1</sup> This distance represents only the amount inventoried outside of the inventoried 10-acre block.

<sup>&</sup>lt;sup>2</sup> This is the direction away from the associated well pad.

Appendix A contains copies of 7.5' USGS quadrangles (map #s 1-5) depicting the well pad project locations. Total area inspected for the four inventories on Ute Tribal land equaled 47.4 acres. Total area inspected for the six inventories on BLM land equaled 83.4 acres.

These cultural resource inventories were conducted to maintain compliance with the National Historic Preservation Act, as amended. Well pad projects CIGE #237, CIGE #238, NBU #314, and NBU #315 are on land owned and controlled by the Ute Indian Tribe (maps #1 and #2 Appendix A), Uintah and Ouray Agency of Fort Duchesne, Utah, and well pad projects NBU #322, NBU #324, NBU #325, NBU #334, NBU #343, and NBU #346 (maps #3-5 Appendix A) are on public land administered by the BLM, Vernal District, Utah. The purpose of these inventories was to locate and record cultural resources in the area of potential effect (APE) of the proposed well projects. If cultural resources were found, their locations were recorded, the appropriate state forms completed (IMAC), a sketch map drawn, and photographs taken. All recorded cultural resources would then be evaluated for eligibility to the National Register of Historic Places (NRHP), and recommendations concerning their management discussed. All site forms were submitted to the Utah Division of State History and copies of the site forms were sent to the appropriate land managers of either the Vernal District BLM or the Ute Indian Tribe.

John M. Scott, staff archaeologist with Metcalf Archaeological Consultants, Inc., conducted the inventories for the BLM well projects on November 3, and 4, 1998 and the Ute Tribal land inventories on November 5, 1998. Mr. Scott was accompanied by Ute Tribal Energy and Mineral Technician Mr. Alvin Ignacio during the inventories on Ute land. All locations were staked and flagged at the time of the fieldwork. Affiliated field notes and data are on file at Metcalf Archaeological Consultants, Inc. Eagle, CO.

## Management Summary

Ute well projects NBU #314 and NBU #315 involved no cultural resources and cultural clearance is recommended for these two projects, as staked at the time of inventory, and with no further stipulations.

On the CIGE #237 project a new prehistoric site with the potential for significant deposits was recorded (42UN2600), a small portion of previously recorded site 42UN2035was encountered, and three isolates were discovered on the associated pipeline. The well pad centerstake for CIGE #237 was moved 50 feet southwest to a recommended location. Moving the pad to the new location and limiting its construction to staked boundaries will effectively avoid any significant portions of 42UN2600. The small portion of 42UN2035 in the original 10-acre inventory block would not have been

impacted by construction of CIGE #237, and with the proposed pad at the new and recommended location, it is even further from the construction area and still will not be impacted. It is additionally recommended that construction of the CIGE #237 well pad be monitored by Ute Tribal Representative Mr. Ignacio, who is familiar with the project. Monitoring is to insure that construction is confined to staked limits. An isolate by definition is not significant and no further work is needed for the three recorded on the proposed pipeline for CIGE #237. The proposed location and access for CIGE #238 was partially staked in previously recorded site 42UN2143, which appears significant and potentially eligible for the National Register. The centerstake was moved 260 feet northwest to a recommended location. This action effectively moved the well pad's APE outside of the site boundaries. In addition to moving the well, the access road was reconfigured further to the north to accommodate the pad's new location and will avoid the site. Although no cultural resources were observed in the proposed pad's new location, it is still close to a known site and in sandy deposition, and because of this, it is recommended that construction of CIGE #238 be confined to the staked limits. It is also recommended that the pad's construction be monitored by a qualified archaeologist and Ute Tribal Representative to inspect for any new deposits that might be uncovered by construction and to insure that construction does not exceed its staked limits. Cultural resource clearance is recommended for CIGE #237 and CIGE #238 with the above stipulations and with approval from the Uintah and Ouray Cultural Rights and Protection Department.

Five of the cultural resource inventories on the BLM land were negative, resulting in no cultural material being recorded. Near the access corridor of the sixth project (NBU #323) one historical site was recorded. This site, 42UN2599, is not significant and not recommended to be eligible for listing on the National Register. Cultural resource clearance is recommended for all six of the BLM well pad projects, as staked at the time of the inventories and depicted on maps #3-5 (Appendix A).

## **Effective Environment**

The project area is located in the Uinta Basin physiographic subdivision of Utah (Stokes 1977). All of the proposed well projects are a few miles south and/or west of the White River. The overall area is rugged and broken by ridges and deeply incised intermittent drainages. Geology of the area is dominated by the Eocene Uintah Formation and is often overlain by alluvail surficial deposits. Occasional outcrops of the Green River Formation may also be present (Hintze 1980). Local vegetation is predominantly sagebrush or shadscale community, which includes low sagebrush, saltbush, rabbitbrush, snakeweed, various cactus, and mixed grasses and forbs. Specific well, access, and pipeline locations are discussed below.

## Well Pad Projects on Ute Tribal Land

## CIGE #237-15-9-21

T.9 R21E Section 15 SW/NW/SE (map 1)

The proposed well is located two miles south of the White River. Its 10-acre inventory block is situated mostly on a degraded flat with an intermittent drainage cutting a prominent channel along the north and east. An east-to-west trending sandstone outcrop is at the center of the east edge of the block. The outcrop's southeast and south edges are dominated by several overhangs and boulders that have been exposed and formed by the scouring action of overbank flooding from the intermittent drainage. Deeply accumulated aeolian sand is on the outcrop's north side. The 10-acre block extends just past the drainage channel on the east and encompasses a small portion of the west-facing slope of a large dune. The general drainage pattern of the area is that of a series of intermittent dendritic-like drainages, which flow north to the White River. Ground surface visibility is excellent at around 85-90% with the vegetation cover consisting predominantly of mixed grasses. With the exception of the above-mentioned sands, the dominant sediment in the 10-acre block is a gray clay hardpan mantled with a very thin sand shadow of varying depth. The project's proposed access leaves an existing north-to-south oil field road in the NE/SE/NE/SW of Section 15. The road will proceed east-southeast to the west edge of the well pad. Additional inventory of 76 meters of linear corridor was required for the proposed access road. The project's proposed pipeline heads north from the pad to an existing east-west road and parallels the road's south side east to an existing well. At the well it turns north and connects to an existing surface pipeline in the NE/SW/NE/SE in Section 15. Additional inventory of 442 meters of linear corridor was required for the proposed pipeline.

## **NBU #314**

T.9S. R.21E. Section 11 C/NE/NE (map 1)

This proposed well pad is positioned on a high bench that overlooks a heavily eroded badlands-like area along the south side of the White River drainage valley. The main channel for the White River is just under a mile to the north. Small clay buttes and cobble-armored hills, with short narrow arroyos are visible below to the east. An existing improved oilfield road cuts through the west side of the 10-acre inventory block and the project's access will be from that road. The project's pipeline will connect to a proposed and staked pipeline of the NBU #316, which parallels the west side of the existing road. The pipeline and access will be entirely within the NBU #314 10-acre block. Neither the access road nor the pipeline required additional inventory. The dominant sediment in the project area appeared to be a sandy clay with a cover of quartzite gravel. Vegetation consisted of a semiarid shrubland that included saltbush, rabbitbrush, mixed grasses, and

forbs. The shrubland covered nearly 40% of the project area, but allowed fair to good surface visibility.

## **NBU # 315**

T9S R21E Section 11 SE/NE (map 1)

Proposed well NBU #315 is located just south of NBU #314 on the same high bench above the White River drainage valley. It is situated away from any of the bench's edges and is relatively flat with a slight slope to the east. An existing oilfield road cuts through the project's west side and its proposed access is from that road. The pipeline tie-in is at the proposed and staked NBU#316 pipeline that parallels the west side of the existing road, and will be entirely within the present project's 10-acre block. No additional inventory was needed for the project's access road or pipeline. Sediments observed in the project area appeared to be a sandy clay with a cover of quartzite gravel. Vegetation consisted of a semiarid shrubland that included saltbush, rabbitbrush, mixed grasses, and forbs. The shrubland covered nearly 40% of the project area, but allowed fair to good surface visibility.

## CIGE #238-20-9-21

T9S R21E Section 20 SE/SE (map 2)

The CIGE #238 well pad project is located on the east side of Cottonwood Wash approximately three miles south of the White River. Cottonwood Wash at this location is a relatively deep channel with exposed sandstone outcrops forming its east side. The staked well area is on the sandy flat between the wash on the west and a prominent sandstone outcrop to the east. The area is covered with a deep sand sheet with low benches of sandstone exposed near the drainage. Vegetation consisted of a semiarid shrubland dominated by sagebrush, greasewood, and rabbitbrush. It covered nearly 30% of the surface, but allowed good ground visibility. The proposed access begins at an existing well access road in the N/NW/SW/SW of Section 21, T.9S., R.21E. It comes off the south side of the road, heads west out of a degraded basin-like area, and up onto the sandy flats to the staked well area. An additional 152 meters of linear corridor was inventoried for the access. The pipeline leaves the proposed pad's northwest edge and snakes north to an existing surface pipeline. An additional 335 meters of linear corridor was inventoried for the pipeline.

## Well Pad Projects on BLM Land

**NBU #323** 

T.9S. R.22E. Section 30 NE/NE (map 3)

This proposed well pad location is staked just west and above Sand Wash approximately 1.25 miles southwest of the White River. This area is heavily dissected by ephemeral drainages, which have exposed large amounts of rimrock. The actual pad area is uneven and broken and drains to the east by small dendritic drainages into Sand Wash. Sand Wash flows north to the White River. Vegetation is a shadscale community with some saltbush, rabbitbrush and snakeweed. It was sparse and covered less than 5% of the ground surface and allowed excellent surface visibility. The observed sediment was a brown clay armored with angular sandstone pebbles. Access for the proposed well pad is from an existing oilfield road located just to the west of the pad. An additional 61 meters was inventoried for the access. The proposed pipeline will leave the north side of the project, cross a deep ephemeral drainage, and then parallel an existing road's east side. It ties into an existing surface line in the NW/NE/NE/NE of the project's section. An additional 152 meters of linear corridor were inventoried for the pipeline.

## **NBU #324**

T9S R22E Section 30 NE/SE (map 3)

NBU #324 is staked in the actual drainage channel of Sand Wash approximately 1.3 miles southwest of the White River. It is up against the wash's east drainage wall below round sided slopes and ledges. The northwest half of the project is in the sandy and gravely flood plain of Sand Wash while the southeast half extends up onto the slopes and ledges. The sediments on the southeast side consist of a slope washed sandy clay with gravels. The sediments of the northwest side consist entirely of alluvial sands, gravels, and cobbles. Vegetation in the drainage is dominated by tall greasewood and willows that form a very dense cover of nearly 80% and allowing only poor ground surface visibility. The slopes on the east side had sparse vegetation and surface visibility was excellent. The proposed access for this project begins near the center of the SW/NW of Section 30. It snakes southwest along the base of the east side of the Sand Wash drainage to its associated well pad. The access corridor required additional inventory of approximately 640 meters. The proposed pipeline will snake north to tie-in near proposed well NBU #325 in the NE/SW/SE of Section 30 and required an additional inventory of 122 meters. The main drainage for the general area is Sand Wash and it drains north to the White River.

## **NBU #325**

T.9S. R.22E. Section 30 NE/NE (map 3)

This proposed well pad project is staked on benches just above the east side of Sand Wash. The location is very uneven and broken. Vegetation cover is sparse, around 15%, and consists of shadscale and mixed grasses. Soil on the pad area consisted of a gray silty clay armored with gray sandstone pebbles. The proposed access starts at the southwest edge of the staked NBU#324 pad location. It snakes south along the east side of the drainage and then angles up onto the east benches to connect with the south edge of its associated pad. Approximately 122 additional meters were inventoried for the access. Sediments observed along the access corridor in Sand Wash consisted of alluvial sands and gravels. Sediments along the access corridor on the east benches appeared to be a clay with gravels. Visibility in the drainage was poor, because of a tall and dense cover (70%) of saltbush, but was excellent on the benches. The proposed pipeline corridor juts southward for a short distance to connect with an existing surface pipeline that crosses the southwest corner of the inventory block. Since the proposed pipeline was entirely within the 10-acre inventory block, no additional inventory was required.

## **NBU #334**

T.10S. R.22E. Section 3 NE/SE (map 5)

This proposed well is located on the east edge of the Bitter Creek Gas Field approximately .4 of a mile west of the White River. The pad is staked against a semicircular ridge system that opens to the north. It is at the head of an intermittent drainage that flows north and eventually into the White River. Ground cover in the pad area was only around 5% consisting mainly of sagebrush, bunch grass, and saltbush. The soil resembled a grayish clay hardpan veneered with sandstone pebbles. The associated access will be from an existing oilfield road that cuts across the center of the proposed pad and did not require any additional inventory. The associated pipeline heads south from the pad, crosses an existing road, and connects to an existing surface pipeline in the SE/SE/SE of the Section 3. Approximately 506 additional meters were inventoried for the pipeline corridor and it crossed terrain similar to that of its associated pad.

## **NBU #343**

T.10S. R.22E. Section 8 NE/NW (map 4)

Proposed NBU #343 is approximately 1.4 miles west of the White River and 1.1 miles east of Sand Wash in the Bitter Creek Gas Field. It is positioned in the curve of an east facing ridge. This area is the head of an unnamed intermittent drainage that flows northeast into a system of dendritic drainages and eventually into the White River. Vegetation includes mixed grasses and forbs with sparse saltbush and sagebrush. It

covered approximately 10% of the ground surface and allowed excellent visibility. The associated access road snakes south to an existing oil field road in the SW/NE of Section 8. It required an additional 373 meters of inventory. The pipeline also runs south from the staked pad to connect to an existing surface pipeline in the NE/SW/NE of the project's section. It required approximately 152 meters of additional inventory. The terrain crossed by both the access and pipeline corridors was similar to that of the associated 10-acre inventory block.

## **NBU #346**

T.10S. R.22E. Section 10 SE/SE (map 5)

This proposed well pad project is staked in the Bitter Creek drainage. Bitter Creek is in a deep and narrow canyon with large amounts of rimrock and down cutting tributary drainages. Bitter Creek flows almost due north into the White River. The pad is staked on the west side of the creek on its flood plain. Steep rock walls and ledges are on the east and west. The canyon bottom is covered with alluvial sand and gravel. Against the west side of the canyon the sand gives way to colluvial loam partially covered with sandstone blocks and boulders. Access will be from an improved dirt road that runs north and south through the canyon and crosses through the pad near its center. The access required no additional inventory. The associated pipeline will leave the northwest corner of the pad and heads north paralleling the existing road's west side to connect to an existing surface line in the vicinity of existing well NBU #293 (NE/SW/NE of Section 10). Approximately 900 meters of the proposed pipeline required additional inventory. Vegetation on the well pad block consists of high greasewood that forms a dense cover with an under story of mixed grasses, forbs and low shrubs. Approximately 50% of the surface was covered with vegetation which allowed only poor-to-fair surface visibility on most of the inventory block. Along the west side of the pad, above the sand bottom, and along the pipeline corridor, vegetation was sparse, covering only 10% of the surface and allowing excellent ground surface visibility.

## Files Search

A files search for all of the well pad project locations was requested from the Utah Division of State History on August 31, 1998. A second files search, involving only the projects on BLM land, was conducted at the BLM, Vernal District Office on November 3, 1998. The locale of the present projects is a highly-developed oil and gas field and the files listed many previously conducted projects and cultural resources for the region. However, only proposed CIGE #238 was in a previously inventoried area. A previously recorded and potentially eligible site (48UN2143) is partly within the CIGE #238 project area. The previously recorded site is named the Ignacio Shelter (Scott 1994) and was recorded in 1994 by John Scott of MAC for the Reliable 3D seismic project (Spath 1994).

It is listed as a moderately dense lithic scatter around a prominent sandstone outcrop in a 39,250 sq. meter area. Included in the site inventory were chipped stone tools, a grinding slab, several bifaces and a rock shelter with rock art. The plotted location of the CIGE #238 inventory block appears to extend 200 feet onto site 48UN2143 and would probably impact the lithic scatter but not the rock shelter or rock art which appears to be at least 200 feet from the east edge of the 10-acre block. The only other site that appeared to be near any of the different project areas was 42UN2035. The southeast corner of the 10-acre inventory block for proposed CIGE #237 protruded less than 100 feet onto that site. 42UN2035 was recorded by James Truesdale (then of MAC) in July of 1992 for the CIGE #171 well pad project (Truesdale 1992). It is described as a large site (156,000 sq. m.) situated in a sequence of sand dunes. Artifacts listed in the site inventory included 17 ceramic sherds, 153 pieces of debitage, and stone tools, including both chipped and groundstone tools. Mr. Truesdale recommended the site to be eligible for listing on the National Register.

Another source of general information for the Uinta Basin, which was consulted prior to field work, is the three volume document *Paradigms and Perspectives, A Class I Overview of Cultural Resources in the Uinta Basin and Tavaputs Plateau* (Spangler 1995). This work provides good overviews of the history of cultural resource work conducted in the region, Uinta Basin cultural chronologies, and an annotated Bibliography. It should be consulted for further information on the cultural resources of the Uinta Basin.

## <u>Methods</u>

The ten proposed Coastal Oil & Gas Company well locations, access roads, and pipelines were plotted on USGS 7.5'quadrangle maps and then inspected for cultural resource material. The access roads and proposed pipelines were investigated by examining the ground surface while walking two zigzag transects. One transect was walked on each side of the staked centerline, so that each side received 50 ft (15 meters) of coverage, equaling a total corridor width of 100 ft (30 meters). When linear corridors paralleled existing disturbance, the entire 100 ft was measured from the edge of the disturbance out. The proposed well locations were inventoried by inspecting a 10-acre block centered on the well pad's *location-to-drill* stake and oriented to the cardinal directions. This 10-acre block was examined by attentively observing the ground surface while walking parallel transects spaced 15-to-20 meters apart across the entire block. Special attention was given to areas of surface disturbance (i.e., rodent activities, previous construction areas, erosional areas). These areas were thoroughly inspected for signs of cultural material.

All recommendations for cultural properties on Ute Tribal land were discussed between the project archaeologist and accompanying Tribal Representative. When the

recommendations involved moving a staked portion of a project, the pertinent information was provided to the contracted survey company, who then made the changes. The changes made in the project staking were observed in the field by either the investigating archaeologist or the tribal representative.

## Results and Recommendations

## Ute Wells

Well projects NBU #314 and NBU #315 involved no cultural resources and cultural clearance is recommended for these two projects, as they are depicted on map 1 (Appendix A) and with no further stipulations. Cultural resources were encountered on the CIGE #237 and CIGE #238 projects and cultural resource clearance is recommended for CIGE #237 and CIGE #238 only with the following stipulations and with the approval of the Uintah and Ouray Cultural Rights and Protection Department.

On the CIGE #237 project a new prehistoric site with the potential to contain significant deposits was recorded (42UN2600), a small portion of previously recorded site 42UN2035 was encountered, and three isolates were discovered on the associated pipeline. The well pad centerstake for the CIGE #237 was moved 50 feet southwest. Moving the pad to the new location and limiting its construction to the staked boundaries will effectively avoid impacting any significant portions of 42UN2600. The portion of 42UN2035 in the original 10-acre inventory block was not in the construction zone of CIGE #237, and with the new location, 42UN2035 is even further from the construction area and will not be impacted. An isolate by definition is not significant and no further work is needed for the three recorded on the associated pipeline. It is further recommended that construction of the well pad be monitored by Ute Tribal Representative Mr. Ignacio, who is familiar with the project. This is to insure that construction does not exceed staked limits.

The proposed location and access of CIGE #238 was partially staked in previously recorded site 42UN2143, which appears significant and potentially eligible for the National Register. The centerstake was moved 260 feet to the northwest and that area inspected. This action effectively moved the well pad's APE outside of the site boundaries (Figure 1). In addition to moving the well, the access road was reconfigured further to the north to accommodate the pad's new location and to avoid the site. Although no cultural resources were observed in the proposed pad's new location, it is still close to a known site in sandy deposition, and because of that, it is recommended that construction of CIGE #238 be confined to the staked limits. It is also recommended that the pad's construction be monitored by a qualified archaeologist and Ute Tribal




Figure 1 CIGE 238 project area showing relationship of new and recommended well pad location to 42UN2143

Representative to inspect for any new deposits that might be uncovered by construction, and to insure that construction does not exceed its staked limits.

## **BLM Wells**

Five of the cultural resource inventories on the BLM land were negative, resulting in no cultural material being recorded. Near the access corridor of the sixth project (NBU #323) one historical site was recorded. This site, 42UN2599, is recommended to be not eligible for listing on the National Register. Cultural resource clearance is recommended for all six of the BLM well pad projects, as staked at the time of the inventories and depicted on maps 3, 4, and 5 (Appendix A).

## **Ute Sites**

#### 42UN2600

This prehistoric site consists of three rock overhangs on the south side of a large sandstone outcrop with a surrounding lithic scatter in a 4239 square meter area (Figure 2). The site is located two miles south of the White River and three miles east of Cottonwood Wash near the head of a major unnamed intermittent drainage. The drainage passes immediately south and east of the site and overbank flooding with wind erosion has exposed and shaped the overhangs on the south side of the outcrop (Figure 3). The three overhangs, which face south and southeast are 2 to 3 meters long and 1 to 1.5 meters high. Immediately north of the outcrop there is a deep sand dune that has good potential for buried deposits. However, most of the artifacts were observed on the south in and around the overhangs where there is very little deposition. Located southeast of the site is

a flat bench-like area covered with a spotty sand shadow, and the lithic scatter extends only a short distance onto this bench. Several previously recorded sites are in the general vicinity; 42UN2035 is located immediately opposite this site on the south side of the drainage.

The lithic scatter is concentrated around the large sandstone outcrop and consists of approximately 50 flakes, six bifaces (Figure 4), one uniface, two manos (Figure 5), and a sparse and diffuse scatter of FCR. Some of the flakes and tools were in two different concentrations (#1 and #2). The concentrations were located below the sandstone overhangs and may be collector piles. Concentration #1 measured approximately 1 x .5 meters and is located south of the sandstone outcrop at the edge of the drainage channel's north bank. This area is slightly sandy and the concentration is under bushes growing along the drainage bank. Its inventory includes three bifaces (2, 3, and 4) with 15 flakes and core fragments, all of quartzite and chert. Concentration #2 measured .5 X .5 meters,




Figure 2 Site overview of 42UN2600 looking NNW (Exp.#4, Rll. #68-98)

and is located at the southeast end of the site just below the drip line of the farthest eastern overhang. Its inventory includes three cores, biface # 5, one uniface, and five flakes, all of quartzite and chert. Neither of these concentrations have potential for buried deposits at their locations. In general, the most common lithic reduction stage observed was tertiary with far fewer decortication and secondary stages present. All but two of the




Figure 3 View of largest overhang at the southeast end of 42UN2600 looking W (Exp. # 15, RII.# 68-98)

bifaces were in the two concentrations. Biface #1 is a small quartzite cobble with black cortex and a yellowish brown interior. It measures 8.7 X 4.2 X 2 cm. Biface #2 has been manufactured from a very fine grained multicolored quartzite pebble. It measures 2 X 3 X 1.7 cm. Biface #3 is of brown chert and measures 9.3 X 4 X 1.7 cm. Biface #4 has been manufactured from a coarse brown chert and measures 5 X 6.5 X 2.5 cm. Biface #5 has been manufactured from brown chert and measures 7 X 5 X 2.5 cm. Biface #6 was manufactured from a coarse grained banded chert and measured .7 X 4.5 X .2. The single uniface measured 6 X 4.5 X 1.5 and was manufactured from brown chert. The groundstone included two manos. Mano #1 is located on the south edge of the site below the overhangs. It is a small, oddly shaped sandstone cobble with only one grinding surface. Mano #2 is on the north east edge of the site above a wind-scoured shallow sandstone alcove. It is a rectangular shaped flat quartzite mano, which has been ground and pecked on one side. The shape and size of the manos can be seen in Figure 5.

This site has not been evaluated as to its eligibility for listing on the National Register, but has potential for intact buried deposits. The present project was originally laid out so that it would impact the east side of the sandstone outcrop and part of the deep dune to the south. The project area has been moved further south and will not impact the dune or the outcrop, but will affect the few flakes on the deflated bench. Only three



**Figure 4** Six bifaces from 42UN2600. The last artifact on the right is an uniface (Exp. #12, RII, #68-98)

flakes were observed in that area and they are on thin hardpan clay that overlays bedrock. The area of the site affected by the present project is not significant and does not contribute to the overall potential significance of the site.

## 42UN2143

This site is a significant multi-component site named the Ignacio Shelter. It was previously recorded by the author in 1994 during the Reliable Exploration's Coastal Oil and Gas 3D Prospect project. During the present project's revisit, an additional projectile point fragment was discovered (Figure 6). Other than the new artifact, the site appeared to be the same as originally recorded.

The site consists of various colored chert and quartzite flakes, four projectile points, one groundstone slab, and several bifaces, all centered around a sandstone outcrop with a rock shelter at its west end. Aeolian sand with good potential for depth and buried deposits also surrounds the outcrop. The site area totals 39,250 square meters. Near the shelter is a brown sandstone panel with a pecked figure that resembles a hunched-back person. A historical material scatter and rock feature are also present. The historical material consists of a sparse scatter of cans and ceramics. The rock feature is a pile of




Figure 5 Two manos observed on site 42UN2600 (Exp. #10, RII. #68-98)

sandstone that has partially collapsed. The prehistoric component inventory lists more than 500 pieces of different colored quartzite, chert and siltstone debitage. A 40% sample indicated that tertiary flakes were dominant with secondary common. Decortication flakes, shatter, and cores were also present, but in substantially fewer amounts. Only two pieces of fire cracked rock (FCR) were observed during the initial recording. The three originally recorded projectile points were corner-notched, but the newly recorded point appears to be side-notched.




Figure 6 New projectile point found on 42UN2143 (Exp. #8, Rll. #68-98)

The rock shelter is at the west end of the sandstone outcrop and is formed by a natural overhang and a large boulder. The shelter measures 3.5 meters (back wall-to-drip line) by 3 meters (sidewall-to-sidewall) and is 1.9 meters high. The ceiling angles back and down from the drip line to a back wall .4 of a meter high. There is a small amount of deposition inside the shelter. The pecked figure is on a panel just outside of the shelter and appears to be badly deteriorated with perhaps 40% destroyed.

This site has been recommended to be potentially eligible for the National Register and as such should not be impacted by development. The original location of the present project was aligned so that it clearly would impact the site's eastern side where there are artifacts and aeolian sands that could contain intact buried cultural deposits. Consequently, it was recommended that the project be moved. A location further to the northwest was selected and inspected, and the project restaked at the new location. Although the new location is nearby, the project's construction will not impact the site (Figure 1).

#### Ute Isolated Finds

#### IF-237/1


This isolate consists of one brown chert uniface fragment. It is located on gray degraded clay hardpan at the south end of an existing well pad. The location has probably been impacted by construction and more recently, heavily sheet washed, and there is no chance for buried deposits. Vegetation was very sparse, but sagebrush and saltbush were in the general area. There are several large sites in the vicinity of this artifact in an environment susceptible to erosion, consequently, it is expected that isolated artifacts would be found outside of the sites. This artifact lacks integrity and is at a location with no chance for buried deposits. The resource is not significant, it has been adequately recorded, and no further work is needed.

#### IF-237/2

This resource consists of three flakes in a 5 X 5 meter area on gray clay hardpan. It is located between an oilfield road immediately on the north and a sand dune immediately on the south. The sand dune is the same dune that site 42UN2600 extends into, but at the dune's south end. This isolate is more than 50 meters away from the most northern artifact of 42UN2600. The flakes include one banded coarse quartzite primary flake and two white chert flakes, 1 primary and 1 secondary. Vegetation is very sparse, but rabbitbrush and greasewood are in the surrounding area. There are several large sites in the vicinity of this artifact in an environment susceptible to erosion, consequently, it is not unexpected for isolates to occur outside of the sites. This artifact is not significant and at a location with no chance for buried deposits. The resource has been adequately recorded and no further work is needed.

#### IF-237/3

This isolate consists of one reddish quartzite cobble fragment that may have been a two-handed mano. It is ground and pecked on one side and measures 14 X 7.5 X 7.5 cm. The artifact is at the east end of a degraded flat and just west of an intermittent



drainage that has cut a channel at the flat's east end. The area has been heavily sheet washed leaving a hardpan of gray silty clay with several loose cobbles on the surface. There is very sparse vegetation, but rabbitbrush and greasewood surround the location. This artifact lacks integrity and is at a location with no chance for buried deposits. It is not significant, it has been adequately recorded, and no further work is needed.

Figure 7 Sketch map of 42UN2599

#### **BLM Sites**

#### 42UN2599

This historic site consists of 19 juniper logs located on a finger-like bench above a drainage to the east (Figure 7). The logs are approximately 30 meters east of an existing oilfield road and 120 meters south of the fence line that marks the boundary between BLM and Ute Tribal property. There are hills with sandstone rimrock west of the road and buttes to the north/northeast. Just eight meters east of the logs there is evidence of mechanical blading and a berm of earth. This may have been a road of some sort, but is




Figure 8 Overview of logs ((42UN2599) looking NNE (Exp. 6, Rll. 68-98)


mechanical blading and a berm of earth. This may have been a road of some sort, but is presently very faint, lacks ruts, and appears to end at this location. The site has good views to the east. The logs are lying side-by-side, aligned east-to-west, and measured between 2.5 and 3.0 meters long (Figure 8). All have axe cut bottoms and the bottoms are thicker (15-16 cm) than the tops. Bark is still present on some of the logs. At the time of discovery, it was thought that the logs could represent a collapsed structure, such as a wickiup, and certainly, they could still be used to construct such a structure. But, a more plausible explanation for their use, is that they were either part of, or were to be used in the fence line that marks the boundary between Ute Tribal land and public land, which is located 120 meters to the north. That fence line is presently constructed with metal poles. The site has been adequately recorded, holds no further information important in history, and no further work is recommended.


#### References Cited


- Hintze, L.
  - 1980 Geologic Map of Utah. Dept.of Natural Resources, Utah Geological and Mineral Survey, Salt Lake City.
- Scott, John M.
  - 1994 Intermountain Antiquities Computer System (IMACS) Site Form, 42UN2143. On file, Utah Division of State History, Salt Lake City.
- Spath, Carl
  - Reliable Exploration's Coastal oil and Gas 3D Prospect on the Uintah Ouray Ute Reservation, T9S, R21E Sections 4-9,16-21, and 28-30, Uintah County, Utah, Class III Cultural Resource Inventory. Metcalf Archaeological Consultants, Inc., Eagle, CO. Manuscript on file, Utah Division of State History, Salt Lake City.
- Stokes, M.
  - 1977 Physiographic Subdivisions of Utah. Dept.of Natural Resources, Utah Geological and Mineral Survey, Salt Lake City.
- Truesdale, James A.
  - 1992 Results of a Class III Cultural Resource Inventory for Coastal Oil and Gas Company Proposed Well Location of CIGE-171 its Access and Flow Line.


    Metcalf Archaeological Consultants, Eagle, CO. Report on file with Utah Division of State History.


APPENDIX A
(Project Location Maps)












APPENDIX B (Site and Isolate Forms)

## WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 01/17/2001	API NO. ASSIGNED: 43-047-33879			
WELL NAME: NBU 315 OPERATOR: COASTAL OIL & GAS CORP ( N0230 ) CONTACT: CHERYL CAMERON	PHONE NUMBER: 43	5-781-7023		
PROPOSED LOCATION:	INSPECT LOCATN	BY: / /		
SENE 11 090S 210E SURFACE: 1798 FNL 0770 FEL	Tech Review	Initials	Date	
BOTTOM: 1798 FNL 0770 FEL	Engineering			
UINTAH NATURAL BUTTES ( 630 )	Geology			
LEASE TYPE: 1-Federal	Surface			
LEASE NUMBER: U-0141317 SURFACE OWNER: 2-Indian				
PROPOSED FORMATION: WSTC				
Plat Bond: Fed [1] Ind[] Sta[] Fee[] (No. U-605382-9  Potash (Y/N)  Plat  Bond: Fed [1] Ind[] Sta[] Fee[] (No. U-605382-9  Noil Shale (Y/N)  Water Permit (No. 43-8496  NRDCC Review (Y/N) (Date:  NA Fee Surf Agreement (Y/N)	R649-3-2. G Siting: 460 Fr R649-3-3. E Drilling Uni Board Cause Eff Date: Siting: 460 Fr	nit NATURAL BU' eneral om Qtr/Qtr & 920' xception	Between Wells  E. Uncomm. Tract.	
COMMENTS: NBU SOP, Separate file.				
STIPULATIONS: DEDFRAL APPROVAL DIL SHALE				




OPERATOR: COASTAL O&G CORP (N0230)

FIELD: NATURAL BUTTES (630)

SEC. 11, T9S, R21E,

COUNTY: UINTAH UNIT: NATURAL BUTTES

CAUSE: 173-14



PREPARED BY: LCORDOVA DATE: 27-JANUARY-2001



Michael O. Leavitt Governor Kathleen Clarke Executive Director Lowell P. Braxton

Division Director

1594 West North Temple, Suite 1210 PO Box 145801 Salt Lake City, Utah 84114-5801 801-538-5340 801-359-3940 (Fax) 801-538-7223 (TDD)

January 29, 2001

Coastal Oil & Gas Corporation PO Box 1148 Vernal, UT 84078

Re: Natural Buttes Unit 315 Well, 1798' FNL, 770' FEL, SE NE, Sec. 11, T. 9 South,

R. 21 East, Uintah County, Utah

#### Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann.§ 40-6-1 et seq., Utah Administrative Code R649-3-1 et seq., and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-33879.

Sincerely,

/John R. Baza

Associate Director

er

**Enclosures** 

cc:

**Uintah County Assessor** 

Bureau of Land Management, Vernal District Office

Operator:	Coastal Oil & Gas Corporation				
Well Name & Number	Natural Buttes Unit 315				
API Number:	4	3-047-33879			
Lease:	U	J-0141317			
Location: SE NE	Sec. 11	T. 9 South	R. 21 East		

#### **Conditions of Approval**

#### 1. General

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

#### 2. Notification Requirements

Notify the Division within 24 hours of spudding the well.

• Contact Carol Daniels at (801) 538-5284.

Notify the Division prior to commencing operations to plug and abandon the well.

• Contact Dan Jarvis at (801) 538-5338

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

- 4. In accordance with Order in Cause No. 190-5(b) dated October 28, 1982, the Operator shall comply with requirements of Rules R649-3-31 and R649-3-27 pertaining to Designated Oil Shale Areas. Additionally, the operator shall ensure that the surface and/or production casing is properly cemented over the entire oil shale interval as defined by Rule R649-3-31. The Operator shall report the actual depth the oil shale is encountered to the Division.
- 5. State approval of this well does not supersede the required federal approval, which must be obtained prior to drilling.

Form 3160-3 (August 1999)

\*(Instructions on Reverse)

# UN'TO STATES DEPARTME\_OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0136 Expires: November 30, 2000

5. Lease Serial No.

APPLICATION FOR PERMIT TO DRILL	JUR REENIER	U-01413	L7
. Type of Work X DRILL REENTI	ER	6. If Indian, Al	lotee or Tribe Name
		Uintah 8	Ouray
Type of Well Oil Well X Gas Well Other	Single Zone Multiple Zone	-	Agreement Name and No.
			Buttes Unit
Name of Operator	V.	8. Lease Name	
bastal Oil & Gas Corporation	3b. Phone No. (include area coo	NBU #31!	
Address	·	J.All Well IV	0.
P.O. Box 1148, Vernal, UT 84078  Location of Well (Report location clearly and in accordance with any St	(435) -781-7023	N/A	1 5 1 4
		Natural	ool, or Exploratory
At surface SE NE	RECEIVED	11. Sec., T., R.	M., or Blk. and Survey or A
At proposed prod. zone 1798 FNL & 770 FEL	JAM 1 1 2001	Ì	11-T9S-R21E
1/50 112 4 //0 12	J. 1. 1 _ 2.001	12. County or P	
Distance in miles and direction from nearest town or post office*	_	1	
19.9 Miles Northwest of		<u>  Uintah</u>	Utah
. Distance from proposed*	16. No. of Acres in lease	17. Spacing Unit dedi	cated to this well
location to nearest			
property or lease line, ft. 770 (Also to nearest drg. unit line, if any)	480		n/a
	19. Proposed Depth	20.BLM/BIA Bond	No. on file
<ol> <li>Distance from proposed location* to nearest well, drilling, completed,</li> </ol>	19.1 Toposed Bopan		
11-1 for an this loops ft	7400'	17.	-605382-9
applied for, on this lease, it.  Refer to Topo "C"		<u> </u>	
. Elevations (Show whether DF, KDB, RT, GL, etc.	22. Approximate date work will sta	1	ated duration
4849.2'Ungraded GL	Upon Approval	I	o Be Determined
he following, completed in accordance with the requirements of Onshore C	24. Attachments Dil and Gas Order No. 1, shall be attached	ed to this form:	
Well plat certified by a registered surveyor.  A Drilling Plan  A Surface Use Plan (if the location is on National Forest System Lands, SUPO shall be filed with the appropriate Forest Service Office).	4. Bond to cover the operation Item 20 above).  5. Operator certification.	ions unless covered by	an existing bond on file (see
<b>N</b>	Name (Printed/Typed)		Date
5. Signuature	**		1/8/01
hely timera	Cheryl Cameron		1,0,01
itle T			
Sr. Regulatory Analyst			<del> </del>
Approved by (Signautre)	Name (Printed/Typed)		Date 03/20/20
Title Assistant Field Manager	Office	MAVAT	• /
Mineral Resources	The state of the s	E. LAN ALL	
application approval does not warrant or certify that the applicant holds lead to onduct operations thereon. Conditions of approval, if any, are attached.			
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a United States any false, fictitious or fraudulent statements or representation	a crime for any person knowlingly and is as to any matter within its jurisdiction	willfully to make to	any department or agenc

MAR 2 6 2001

DIVISION OF OIL, GAS AND MINING

COAs Page 1 of <u>4</u> Well No.: NBU 315

# CONDITIONS OF APPROVAL APPLICATION FOR PERMIT TO DRILL

Company/Operator: Coastal Oil & Gas Corporation
Well Name & Number: NBU 315
API Number: <u>43-047-33879</u>
Lease Number: U-0141317
Location: <u>SENE</u> ) Sec. <u>11</u> T. <u>09S</u> R. <u>21E</u>
Agreement: Natural Buttes Unit

COAs Page 2 of 4 Well No.: NBU 315

### CONDITIONS OF APPROVAL FOR NOTICE TO DRILL

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Be aware fire restrictions may be in effect when location is being constructed and/or when well is being drilled. Contact the appropriate Surface Management Agency for information.

### A. <u>DRILLING PROGRAM</u>

### Casing Program and Auxiliary Equipment

As a minimum, the usable water resources shall be isolated and/or protected by having a cement top for the production casing at least 200 ft. above the base of the usable water zone, identified at 344 ft.

COAs Page 3 of 4 Well No.: NBU 315

## SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

Coastal Oil and Gas Corporation (Coastal) will assure the Ute Tribe that any/all contractors and subcontractors have acquired a current Tribal Business License and have updated "Access Permits" prior to construction. All Coastal personnel, contractors and subcontractors will have these permits in their vehicles at all times. Companies that have not complied with this COA will be in violation of the Ute Tribal Business License Ordinance, and will be subject to fines and penalties.

Coastal employees, representatives, and/or authorized personnel (subcontractors) shall not carry firearms on their person or in their vehicles while working on the Uintah and Ouray Indian Reservation.

Coastal employees and/or authorized personnel (subcontractors) in the field will have approved applicable APDs and/or ROW permits/authorizations on their person(s) during all phases of construction.

Coastal will notify the Ute Tribe and Bureau of Indian Affairs (BIA) in writing of any requested modification of APDs or Rights-Of Way (ROW). Coastal shall receive written notification of authorization or denial of the requested modification. Without authorization, Coastal will be subject to fines and penalties.

The Ute Tribe Energy & Minerals Department shall be notified in writing 48 hours in advance of any construction activity. The Ute Tribal office is open Monday through Thursday. A Tribal Technician is to routinely monitor construction. Coastal shall make arrangements with the Ute Energy & Minerals Department for all monitoring that will exceed regular working hours for Tribal Technicians. A qualified Archaeologist accompanied by a Tribal Technician will monitor any trenching required for the construction of the pipeline. Coastal is to inform contractors to maintain construction of the pipelines within approved 30 foot right of ways.

A corridor ROW, 30 feet wide, shall be granted for pipelines or access roads. The constructed travel width of the access road will be limited to 18 feet. Upon authorization by the Ute Tribe Energy & Minerals Department, the ROW may be wider where sharp curves; deep cuts and fills occur; or, where intersections with other roads are required. Upon completion of each pipeline in the corridor an adequate description of the pipeline will be filed with the Ute Tribe Energy & Minerals Department.

Upon completion of the pertinent APD and ROWs, Coastal will notify the Ute Tribe Energy & Minerals Department for a Tribal Technician to verify the Affidavit of Completion.

Production waters, oil, and other byproducts shall not be placed on access roads or the well pad.

All vehicular traffic, personnel movement, construction and restoration operations will be confined to the areas examined and approved and to the existing roadways and/or evaluated access routes.

COAs Page 4 of 4 Well No.: NBU 315

Coastal will implement "Safety and Emergency Plan" and ensure plan compliance.

Coastal shall stop construction activities and notify personnel from the Ute Tribe Energy & Minerals Department and BIA if cultural remains including paleontologic resources (vertebrate fossils) are exposed or identified during construction. The Ute Tribe Department of Cultural Rights and Protection and the BIA will provide mitigation measures prior to allowing construction.

Coastal employees and/or authorized personnel (subcontractors) will not be allowed to collect artifacts and paleontologic fossils. No significant cultural resources shall be disturbed.

Coastal will control noxious weeds on the well site and ROWs. Coastal will be responsible for noxious weed control if weeds spread from the project area onto adjoining land.

Reserve pits will be lined with an impervious synthetic liner. About 17 rods of fence will be constructed around the reserve pit until it is backfilled. Prior to backfilling the reserve pit, all fluids will be pumped from the pit into trucks and hauled to approved disposal sites. When the reserve pits are backfilled, the surplus oil and mud, etc., will be buried a minimum of 3 feet below the surface of the soil.

A closed system will be used during production. This means that production fluids will be contained in leak-proof tanks. All production fluids will be disposed of at approved disposal sites.

Surface pipelines will be constructed to lay on the soil surface. The ROW will not be bladed or cleared of vegetation without authorization of the BIA. Where surface pipelines do not parallel roads but cross country between stations, they shall be welded in place at well sites or on access roads. They shall be pulled between stations with suitable equipment. Vehicles shall not use pipeline ROWs as access roads unless specifically authorized.

Buried pipelines shall be buried a minimum of 3 feet below the soil surface. After construction is completed the disturbed area shall be contoured to blend into the natural landscape and be reseeded between September 15 and November 1 of the year following construction with perennial vegetation seed mixture provided by the BIA or Ute Tribe.

Before the site is abandoned, Coastal will be required to restore the well site and ROWs to near their original state. The disturbed areas will be reseeded with desirable perennial vegetation.

Soil erosion will be mitigated by reseeding all disturbed areas.


Do not abandon  SUBMIT  1. Type of Well:  Oil Well  Gas Well  2. Name of Operator COAST CONTA EMAIL  3a. Address P.O. BOX 1 VERNAL, U	BEPARIMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals  SUBMIT IN TRIPLICATE- Other Instructions on reverse side  Type of Well: Oil Well  Gas Well  Other  Name of Operator COASTAL OIL & GAS CORPORATION CONTACT: CHERYL CAMERON OPERATIONS EMAIL: Cheryl.Cameron@CoastalCorp.com				
	PPROPRIATE BOX(ES) TO			OR1, OR O	THER DATA
If the proposal is to deepen of Attach the Bond under which following completion of inva- testing has been completed. determined that the site is re-	Accep Utah [	Deepen Fracture Treat New Construction Plug and Abandon Plug Back nent details, including estimat lly, give the subsurface locatic ide the Bond No. on file with ults in multiple completion or filed only after all requirement	ons and measured and true the BLM/BIA. Required recompletion in a new int ints, including reclamation	andon  posed work and evertical depths subsequent reporterval, a Form 31, have been com	of all pertinent markers and zones. rts shall be filed within 30 days 60-4 shall be filed once
certify that the applicant holds le Which would entitle the applican Title 18 U.S.C. Section 1001 an States any false, fictitious or fra	re attached. Approval of this notice or	loes not warrant or the subject lease  or  or  or  or  or  or  or  or  or  o	itle  ffice  owingly and willfully to n risdiction	nake to any depa	

4/26/01

## COASTAL OIL & GAS CORPORATION

### DRILLING PROGRAM

COMPANY NAME	Coastal Oil & Gas Corporation	DATE	April 26, 2001			
WELL NAME	NBU #315	TD	7,400' MD/TVD			
FIELD NBU	COUNTY Uintah STATE U	tah	ELEVATION 4,800'	KB		
SURFACE LOCATION	1798' FNL & 770' FEL, Section 11 T9S-R21E				BHL	Straight Hole
OBJECTIVE ZONE(S)	Wasatch					
ADDITIONAL INFO	-					



## COASTAL OIL & GAS CORPORATION DRILLING PROGRAM

#### CASING PROGRAM

							DESIGN FACTO	DRS
	SIZE	INTERVAL	WT.	GR.	CPLG.	BURST	COLLAPSE	TENSION
CONDUCTOR	14"	0-40'						
	1					2950	1370	263000
SURFACE	8-5/8"	0-250'	24#	K-55	STC	21.03	11.71	4.70
						5350	4960	180000
PRODUCTION*	4-1/2"	0-TD	11.6#	K-55	LTC	2.05	1.29	1.33

- 1) Maximum Anticipated Surface Pressure (MASP) (Conductor and Surface Casings) = (Frac Gradient at Shoe Gas Gradient (0.115 psi/ft))(TVD)
- 2) MASP (Int Casing) = Pore Pressure at Next Casing Point (Gas Gradient x TVD of Next Casing Point x 0.67) (Mud Weight x TVD x 0.052 x 0.33)
- 3) MASP (Prod Casing) = Pore Pressure (Gas Gradient x TVD of Production Interval)

(Burst Assumptions: FG @ 8-5/8" shoe = 13.0 ppg, Max Pore Pressure = 9.0 ppg EMW)

(Collapse Assumption: Fully Evacuated Casing, Max MW)

(Tension Assumptions: Air Weight of Casing, 50,000 lbs overpull)

#### **CEMENT PROGRAM**

		FT. OF FILL	DESCRIPTION	SACKS	EXCESS*	WEIGHT	YIELD
SURFACE		250	Class G + 2% CaCl <sub>2</sub> + 0.25 lb/sk Cello	140	35%	15.80	1.17
			Flake	5 0			
PRODUCTION	LEAD	4975	Premium Lite II + 3 lb/sk CSE	650	100%	11.00	3.44
			+ 0.5% Sodium Metasilicate	1 1			
		•	+ 10% Gel + 0.25 lb/sk Cello Flake	1			
			+ 3% Salt + 3 lb/sk Kol Seal				
	TAIL	2425	50/50 POZ + 0.1% R-3 + 1% EC-1	790	75%	14.5	1.23
			+ 0.2% Sodium Metasilicate				
			+ 2% Gel + 0.5% FL-25				

+ 3% Salt

#### **FLOAT EQUIPMENT & CENTRALIZERS**


SURFACE

Guide shoe, 1 jt, float collar. Centralize first 3 joints & every other joint to surface with bow spring centralizers. Thread lock FE up to & including pin end of FC.

PRODUCTION

Sure-seal float shoe, 1 jt, Sure-seal float collar. Centralize first 3 joints & every other joint to top of tail cement with bowspring centralizers.

#### WELLHEAD EQUIPMENT



<sup>\*</sup> or 15% over caliper log

Page 3/3

## COASTAL OIL & GAS CORPORATION DRILLING PROGRAM

#### BIT PRO

BIT PROGRAM						
		ROCK BI	T & PDC BIT PRO	GRAM		
INTERV	AL HOLE	BIT MFG &			NZLS	COMMENTS
Surface H		Vario	us			
Surf Csg -	- TD 7-7/8"	SEC X			16-16-16	
			Aerated		-	
						****
					<u> </u>	
<u> </u>		I			<u></u>	
If an additional bi	it is required use anothe	er insert.				
<del></del>						
GEOLOGICAL DATA						
LOCCING.						
LOGGING:						
	Depth			Log T	уре	
	SC - TD	Ì		Platform E		
		<u> </u>				
MUD LOGGER:	SC - TD					
SAMPLES:	As per Geol	ogy				
CORING:	NA					
DST:	NA					
MUD PROGRAM						
			WATER		***	
DEPTH	TYPE	MUD WT		SCOSITY		TREATMENT
0-Trona	Air/Mist	NA	NA			Polymer, Gel
(0 - +/-2,000')						Gyp, Lime
Trona-TD	Aerated Water	NA	NC NC	NA	Pr	olymer, Gyp, Lime
(+/- 2,000' - TD)				107		symes, Oyp, Line
(1, 2,000 10)						
Circulate hole un	ntil clean @ TD. Spot b	rine pill at TD fo	r logs and casing.			<u> </u>
						<u> </u>
ADDITIONAL INFORMATIO	NM					
ADDITIONAL INFORMATIO	43					
Test casing head t	to 750 psi after installing.	Test surface casi	ng to 1,500 psi prior to	drilling out.		
	th one annular and 2 rams					d on chart recorder &
tour sheet. Function	on test rams on each trip.	Maintain safety v	valve & inside BOP on	rig floor at a	ill times. Kelly to	be equipped with upper
& lower kelly valve						
	every 1,500' from surface	casing shoe to T	D. Maximum allowabl	e hole angle	is 5 degrees.	
Treat for corrosic	on as per plan.				<u> </u>	
PROJECT ENGINEER:					DATE:	
. MODEOT ENGINEER.	Christa Yir	1				
PROJECT MANAGER:					DATE:	

Darrell Molnar

## STATE TITAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL GAS AND MINING

DIVISION OF OIL, GAS AND MINING	5. LEASE DESIGNATION AND SERIAL NUMBER:
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do not use this form for proposals to drift new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drift horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.	7. UNIT or CA AGREEMENT NAME:
1 Type of WEIL	8. WELL NAME and NUMBER:
OIL WELL GAS WELL OTHER	Exhibit "A"
2. NAME OF OPERATOR:	9. API NUMBER:
El Paso Production Oil. & Gas Company  3. ADDRESS OF OPERATOR:  PHONE NUMBER:	10. FIELD AND POOL, OR WILDCAT:
South 1200 East City Vernal STATE Utah zip 84078 435-789-4433	
4. LOCATION OF WELL FOOTAGES AT SURFACE:	COUNTY:
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN:	STATE: UTAH
CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
NOTICE OF INTENT ACIDIZE DEEPEN	REPERFORATE CURRENT FORMATION
(Submit in Duplicate)  ALTER CASING  FRACTURE TREAT	SIDETRACK TO REPAIR WELL
Approximate date work will start: CASING REPAIR NEW CONSTRUCTION	TEMPORARILY ABANDON
CHANGE TO PREVIOUS PLANS OPERATOR CHANGE	TUBING REPAIR
CHANGE TUBING PLUG AND ABANDON	VENT OR FLARE
SUBSEQUENT REPORT CHANGE WELL NAME PLUG BACK (Submit Original Form Only)	WATER DISPOSAL
Date of work completion:  CHANGE WELL STATUS  PRODUCTION (START/RESUME)	WATER SHUT-OFF
COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL.SITE	X OTHER Name Change
CONVERT WELL TYPE RECOMPLETE - DIFFERENT FORMATION	1
2. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volume	
As a result of the merger between The Coastal Corporation and	d a wholly owned
subsidary of El Paso Energy Corporation, the name of Coastal	Oil & Gas Corporation
has been changed to El Paso Production Oil & Gas Company effe	ective March 9, 2001.
See Exhibit "A"	
Rand # 400JU0708	
Bond # 400JU0708  Coastal Oil & Gas Corporation	
John T Elzner TITLE Vice Presi	dent
SIGNATURE DATE <u>Vib-15-01</u>	
El Paso Production Oil & Gas Company	
NAME (PLEASE PRIM) John T Elzner HILE Vice Presi	dent
DATE 06-15-01	
his space for State use only)	RECEIVED

JUN 19 2001

PAGE 1

## Office of the Secretary of State

I, HARRIET SMITH WINDSOR, SECRETARY OF STATE OF THE STATE OF DELAWARE, DO HEREBY CERTIFY THE ATTACHED IS A TRUE AND CORRECT COPY OF THE CERTIFICATE OF AMENDMENT OF "COASTAL OIL & GAS CORPORATION", CHANGING ITS NAME FROM "COASTAL OIL & GAS CORPORATION" TO "EL PASO PRODUCTION OIL & GAS COMPANY", FILED IN THIS OFFICE ON THE NINTH DAY OF MARCH, A.D. 2001, AT 11 O'CLOCK A.M.



11.1N 1 2001

DIVISION OF DIL. GAS AND MINING



Warriet Smith Windson, Secretary of State

AUTHENTICATION: 1061007

DATE: 04-03-01

0610204 8100

010162788

#### CERTIFICATE OF AMENDMENT

OF

#### CERTIFICATE OF INCORPORATION

COASTAL OIL & GAS CORPORATION (the "Company"), a corporation organized and existing under and by virtue of the General Corporation Law of the State of Delaware, DOES HEREBY CERTIFY:

FIRST: That the Board of Directors of the Company, by the unanimous written consent of its members, filed with the minutes of the Board, adopted a resolution proposing and declaring advisable the following amendment to the Certificate of Incorporation of the Company:

RESOLVED that it is deemed advisable that the Certificate of Incorporation of this Company be amended, and that said Certificate of Incorporation be so amended, by changing the Article thereof numbered "FIRST." so that, as amended, said Article shall be and read as follows:

"FIRST. The name of the corporation is El Paso Production Oil & Gas Company."

SECOND: That in lieu of a meeting and vote of stockholders, the stockholders entitled to vote have given unanimous written consent to said amendment in accordance with the provisions of Section 228 of the General Corporation Law of the State of Delaware.

THIRD: That the aforesaid amendment was duly adopted in accordance with the applicable provisions of Sections 242 and 228 of the General Corporation Law of the State of Delaware.

IN WITNESS WHEREOF, said COASTAL OIL & GAS CORPORATION has caused this certificate to be signed on its behalf by a Vice President and attested by an Assistant Secretary, this 9th day of March 2001.

COASTAL OIL & GAS CORPORATION

David L. Siddal Vice President

Attest:

largaret E. Roark, Assistant Secretary

STATE OF DELAWARE SECRETARY OF STATE DIVISION OF CORPORATIONS FILED 11:00 AM 03/09/2001

IUN 19 2001



## United States Department of the Interior

#### **BUREAU OF LAND MANAGEMENT**

Utah State Office P.O. Box 45155 Salt Lake City, UT 84145-0155

## RECEIVED

JUL 1 2 2001

DIVISION OF OIL, GAS AND MINING

In Reply Refer To: 3106 UTSL-065841 (UT-924)

JUL 1 0 2001 -

#### **NOTICE**

El Paso Production Oil & Gas Company

Nine Greenway Plaza

Houston TX 77046-0095

Oil and Gas

#### Name Change Recognized

Acceptable evidence has been received in this office concerning the name change of <u>Coastal Oil & Gas Corporation</u> into <u>El Paso Production Oil & Gas Company</u> with <u>El Paso Production Oil & Gas Company</u> being the surviving entity.

For our purposes, the name change is recognized effective March 9, 2001.

The oil and gas lease files identified on the enclosed exhibit have been noted as to the name change. The exhibit was compiled from a list of leases obtained from our computer program. We have not abstracted the lease files to determine if the entities affected by this name change hold an interest in the leases identified nor have we attempted to identify leases where the entitities are the operator on the ground maintaining no vested recorded title or operating rights interests. We will be notifying the Minerals Management Service and all applicable Bureau of Land Management offices of the change by a copy of this notice. If additional documentation for changes of operator are required by our Field Offices, you will be contacted by them.

If you identify additional leases in which the entities maintain an interest, please contact this office and we will appropriately document those files with a copy of this Notice.

Due to the name change, the name of the principal/obligor on the bond is required to be changed from Coastal Oil & Gas Corporation to El Paso Production Oil & Gas Company. You may accomplish this either by consent of surety rider on the original bond or a rider to the original bond. The bonds are held in Wyoming and Colorado.

Opolonia L. Abeyta Acting Chief, Branch of Minerals Adjudication

#### Enclosure

1. Exhibit of Leases (1 pp)

cc: Moab Field Office

Vernal Field Office

MMS, Reference Data Branch, MS3130, PO Box 5860, Denver CO 80217

State of Utah, DOGM, Attn: Jim Thompson (Ste. 1210), Box 145801, SLC UT 84114

Teresa Thompson (UT-922)

Joe Incardine (UT-921)

### **Exhibit of Leases**

UTUSL-065841A	UTU-47172	UTU-74415	UTU-53860
UTU-28652	UTU-50687	UTU-74416	UTU-66401
UTU-37943	UTU-52298	UTU-75091	UTU-67868
UTU-44089	UTU-0109054	UTU-75096	UTU-65389
UTU-44090A	UTU-0143511	UTU-75097	UTU-77084
UTU-61263	UTU-0143512	UTU-75673	UTU-61430
UTU-00343	UTU-38401	UTU-76259	UTU-72633
UTU-02651	UTU-38411	UTU-76260	UTU-72650
UTU-02651B	UTU-38418	UTU-76261	UTU-49692
UTU-0142175	UTU-38419	UTU-76493	UTU-57894
UTU-70235	UTU-38420	UTU-76495	UTU-76829
UTU-70406	UTU-38421	UTU-76503	UTU-76830
UTU-74954	UTU-38423	UTU-78228	UTU-76831
UTU-75132	UTU-38424	UTU-78714	
UTU-75699	UTU-38425	UTU-78727	
UTU-76242	UTU-38426	UTU-78734	
UTU-78032	UTU-38427	UTU-79012	
UTU-4377	UTU-38428	UTU-79011	
UTU-4378	UTU-53861	UTU-71694	
UTU-7386	UTU-58097	UTU-00576	
UTU-8344A	UTU-64376	UTU-00647	
UTU-8345	UTU-65222	UTU-01470D	
UTU-8347	UTU-65223	UTU-0136484	
UTU-8621	UTU-66746	UTU-8344	
UTU-14646	UTU-67178	UTU-8346	
UTU-15855	UTU-67549	UTU-8648	
UTU-25880	UTU-72028	UTU-28212	
UTU-28213	UTU-72632	UTU-30289	
UTU-29535	UTU-73009	UTU-31260	
UTU-29797	UTU-73010	UTU-33433	
UTU-31736	UTU-73013	UTU-34711	
UTU-34350	UTU-73175	UTU-46699	
UTU-34705	UTU-73434	UTU-78852	
UTU-37116	UTU-73435	UTU-78853	
UTU-37355	UTU-73444	UTU-78854	
UTU-37573	UTU-73450	UTU-075939	
UTU-38261	UTU-73900	UTU-0149767	
UTU-39223	UTU-74409	UTU-2078	
UTU-40729	UTU-74410	UTU-44426	
UTU-40736	UTU-74413	UTU-49530	
UTU-42469	UTU-74414	UTU-51026	

#### **OPERATOR CHANGE WORKSHEET**

#### **ROUTING**

110 0 122. 4	
1. GLH	4-KAS
2. CDW	5-LP /
3. JLT	6-FILE

06/21/2001

608186-0143

Business Number:

Enter date after each listed item is completed

Change of Operator (Well Sold)

Is the new operator registered in the State of Utah:

Designation of Agent

Operator Name Change (Only)

X Merger

FROM: (Old Operator): COASTAL OIL & GAS CORPORATION		IIU: (Ne	w Operator):			
CASTAL OIL & GAS CORPORATION		FL PASO	PRODUCTIO	N OIL & GA	S COMI	PANY
ddress: 9 GREENWAY PLAZA STE 2721		Address:	9 GREENWA	Y PLAZA S	TE 2721	RM 2975
Address: 9 GREENWAY PLAZA STE 2721	<del></del>	7 Iddi ess.	) OXEDET (VI			
IOUSTON, TX 77046-0995		HOUSTO	N, TX 77046-0	)995		
hone: 1-(713)-418-4635		Phone:	1-(832)-676-4	1721		
account N0230		Account	N1845			
1025 5						
	CA No.	Unit:	NATURAL I	BUTTES		
WELL(S)			Tana a marini	Tr n A CE	IXVIII T	Taxaba I
	API	ENTITY		LEASE	WELL TYPE	WELL STATUS
NAME	NO	NO	RNG	TYPE FEDERAL	GW	APD
NBU 315	43-047-33879	99999	11-09S-21E 12-09S-21E		GW	P
NBU 57-12B	43-047-30464	2900 2900	12-09S-21E 12-09S-21E		GW	P
NBU 63N-3	43-047-31097 43-047-30550	2900	13-09S-21E	FEDERAL		P
CIGE 61-13-9-21	43-047-30350	2900	13-09S-21E 13-09S-21E	FEDERAL		P
CIGE 125-13-9-21	43-047-32084	2900	13-09S-21E	FEDERAL		P
NBU 121	43-047-32303	2900	13-09S-21E	FEDERAL		P
NBU 122	43-047-32305	2900	13-09S-21E	FEDERAL		P
CIGE 111D-13-9-21	43-047-32918	2900	13-09S-21E	FEDERAL		P
CIGE 214-13-9-21	43-047-33880	2900	13-09S-21E	FEDERAL		P
NBU 318 NBU 317	43-047-33921	99999	13-09S-21E	FEDERAL		APD
NBU CIGE 60-14-9-21	43-047-30549	2900	14-09S-21E	FEDERAL		P
NBU 65	43-047-31099	2900	14-09S-21E	FEDERAL		P
CIGE 170-14-9-21	43-047-32403	2900	14-09S-21E	FEDERAL	GW	P
CIGE 199-14-9-21	43-047-32801	2900	14-09S-21E	FEDERAL	GW	P
NBU CIGE 91D-15-9-21J	43-047-31151	2900	15-09S-21E	FEDERAL		P
NBU 123	43-047-31974	2900	15-09S-21E	FEDERAL		P
CIGE 163-15-9-21	43-047-32192	2900	15-09S-21E	FEDERAL		P
NBU 191	43-047-32298	2900	15-09S-21E	FEDERAL	GW	P
CIGE 171-15-9-21	43-047-32348	2900	15-09S-21E	FEDERAL	GW_	P
OPERATOR CHANGES DOCUMENT.						
1. (R649-8-10) Sundry or legal documentation wa	a manipul from the EODM	IFD operate	or on:	06/19/2001	<b>!</b>	

The new company has been checked through the Department of Commerce, Division of Corporations Database on:

YES

5.	If NO, the operator was contacted contacted on:  N/A
6.	Federal and Indian Lease Wells: The BLM and or the BIA has approved the (merger, name change, or operator change for all wells listed on Federal or Indian leases on:  07/10/2001
7.	Federal and Indian Units: The BLM or BIA has approved the successor of unit operator for wells listed on: 07/10/2001
8.	Federal and Indian Communization Agreements ("CA"): The BLM or the BIA has approved the operator change for all wells listed involved in a CA on:  07/10/2001
9.	Underground Injection Control ("UIC")  The Division has approved UIC Form 5, Transfer of Authority to Inject, for the enhanced/secondary recovery unit/project for the water disposal well(s) listed on:  N/A
D	ATA ENTRY:
1.	Changes entered in the Oil and Gas Database on: 07/26/2001
2.	Changes have been entered on the Monthly Operator Change Spread Sheet on: 07/26/2001
3.	Bond information entered in RBDMS on:  N/A
4.	Fee wells attached to bond in RBDMS on:  N/A
SI	TATE BOND VERIFICATION:
1.	State well(s) covered by Bond No.:  N/A
FI	EDERAL BOND VERIFICATION:
1.	Federal well(s) covered by Bond No.:  WY 2793
F	EE WELLS - BOND VERIFICATION/LEASE INTEREST OWNER NOTIFICATION:
	(R649-3-1) The NEW operator of any fee well(s) listed covered by Bond No:  N/A
2.	The <b>FORMER</b> operator has requested a release of liability from their bond on:  N/A  N/A
3.	(R649-2-10) The <b>FORMER</b> operator of the Fee wells has been contacted and informed by a letter from the Division of their responsibility to notify all interest owners of this change on:
	LMING: All attachments to this form have been MICROFILMED on:
	LING: ORIGINALS/COPIES of all attachments pertaining to each individual well have been filled in each well file on:
<u> </u>	OMMENTS: Master list of all wells involved in operator change from Coastal Oil & Gas Corporation to El Paso
Pr	oduction Oil and Gas Company shall be retained in the "Operator Change File".
	·

Form 3160-5

(August 1999)	UNITED STATES  DEPARTMENT OF THE INTERIOR  BUREAU OF LAND MANAGEMENT				OMB NO. 1004-0135 Expires: November 30, 2000  5. Lease Serial No.			
	SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					r Tribe Name		
		PLICATE - Other instru			U & O  7. If Unit or CA/Agree NBU	ement, Name and/or No.		
l. Type of Well	☑ Gas Well ☐ Oth	er			8. Well Name and No. NBU 315			
2. Name of Ope EL PASO I	rator PRODUCTION	Contact:	CHERYL CAMERON9 E-Mail: Cheryl.Cameron@0		. API Well No. om 43-047-33879			
3a. Address P.O. BOX VERNAL,			3b. Phone No. (include area cod Ph: 435.781.7023 Fx: 435.789.4436	le)	10. Field and Pool, or Exploratory NATURAL BUTTES			
4. Location of V	Vell (Footage, Sec., T.	, R., M., or Survey Description	i)		11. County or Parish,	and State		
Sec 11 T9	S R21E Mer SENE	1798FNL 770FEL			UINTAH COUN	TY, UT		
	12. CHECK APPE	OPRIATE BOX(ES) T	O INDICATE NATURE OF	NOTICE, R	EPORT, OR OTHE	R DATA		
TYPE OF	SUBMISSION		TYPE	OF ACTION				
	C	☐ Acidize	□ Deepen	☐ Produc	tion (Start/Resume)	■ Water Shut-Off		
☐ Notice of	Intent	☐ Alter Casing	☐ Fracture Treat	☐ Reclam	ation	■ Well Integrity		
Subseque	ent Report	□ Casing Repair	☐ New Construction	☐ Recomplete		☑ SPUD		
☐ Final Ab	andonment Notice	☐ Change Plans	□ Plug and Abandon	on				
		☐ Convert to Injection	□ Plug Back	■ Water I	Disposal			
If the propose Attach the Bo following con testing has be	al is to deepen directions and under which the wor	ally or recomplete horizontally will be performed or provide operations. If the operation re- pandonment Notices shall be fi	ont details, including estimated start, give subsurface locations and mee the Bond No. on file with BLM/B esults in a multiple completion or reled only after all requirements, incl	asured and true v BIA. Required su ecompletion in a	bsequent reports shall be new interval a Form 316	filed within 30 days 0-4 shall be filed once		
4/28/01 M SPUD ON	IIRU Bill Martin Air r 4/26/01.		The same of the sa					
7/27/01 Drill 12 1/4" surface hole to 279'. RIH w/ 275 Cmt w/ 155 sx G cmt, 2% CaCl + 1/4#/sk Cello Flake, yield.			of 8 5/8" K-55 csg. 16.0 ppg, 1.15		7 % a 3 2001			
					DIVISION OIL, GAS AND			

14. I hereby certify that the foregoing is true and correct.  Electronic Submission #6017 verified For EL PASO PRODUC	by the BLM Well Information System TION, sent to the Vernal	
Name (Printed/Typed) CHERYL CAMERON	Title OPERATIONS	
Signature held Commelia	Date 07/27/2001	
THIS SPACE FOR FEDERA	L OR STATE OFFICE USE	
Approved By	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Form 3 160-5 (August 1999)

# UN!" "D STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires Inovember 30, 2000

Lease Serial No.

U-0141317

### SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this for abandoned well.		6. If Indian, Allottee or Tribe Name U&O			
SUBMIT IN TRIPLIC	side	7. If Unit or CA/Agreement, Name and/or No.  Natural Buttes Unit			
1. Type of Well  Oil Well  Gas Well  Name of Operator		8. Well Name and No.  NBU #315  9. API Well No.			
Coastal Oil & Gas Corporatio  3a. Address 1368 South 1200 East Verna  4. Location of Well (Footage, Sec., 1  SENE Section 11-T9S-R21E	area code)	43-047-33879  10. Field and Pool, or Exploratory Area  Natural Buttes  11. County or Parish, State  Uintah County, Utah			
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE C	F NOTICE, F	EPORT, OR OTHER DATA	
TYPE OF SUBMISSION			E OF ACTION		
Notice of Intent  Subsequent Report  Final Abandonment Notice	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Reclamati Recomple Temporari Water Dis	ly Abandon Summary posal		
13. Describe Proposed or Completed Ope	I rations (clearly state all pertines ally or recomplete horizontally, rk will be performed or provide	nt details, including estimated give subsurface locations and e the Bond No. on file with 1	starting date of measured and tr BLM/BIA. Requ	any proposed work and approximate duration thereof, use vertical depths of all pertinent markers and zones, are subsequent reports shall be filed within 30 days	

following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.

Finished drilling from 275' to 6900'. Ran 4 1/2" 11.6# K-55 Csg. Pmp 468 Sx Lead Hi-lift "G" Cmt w/Adds. Pmp 750 sx tail 50/50 Poz "G" Cmt w/Adds. Float Held. Lost Circ. Last 10 Bbls of Disp. No Cement to Surface. Finish Nipple Dwn BOP N/U 11" 3M X 7-1/16" 5M Tbg head & Test. Clean mud pits.

Released rig on August 5, 2001 at 2:00 pm.

14. I hereby certify that the foregoing is true and correct	L mid-	
Name (Printed/Typed) Sheila Upchego	Title	Regulatory Analyst
Signature (Carlos Incolumn)	Date	August 8, 2001
THIS SPACE	E FOR FEDERAL OR STA	TE USE
Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not certify that the applicant holds legal or equitable title to those rights in the su which would entitle the applicant to conduct operations thereon.	a)ject icase	
which would entitle the applicant to conduct operations thereon.  Title 18 U.S.C. Section 1001, make it a crime for any person kn	lowingly and willfully to ma	ke to any department or agency of the United States any

false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

HAX	1
2	;
435	֡֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜
8	,
4436	
ã	í

<u>.</u> 2

<u>(435</u>) 781-7023

STATE OF UTAH
DIVISION OF OIL, GAS AND MINING
ENTITY ACTION FORM - FORM 6

OPERATOR	El Paso Production Co. P.O. Box 1148				
ADDRESS					
	Vernal, UT 84078				

OPERATOR ACCT. NO.	. N	1845
--------------------	-----	------

1071011	T										
ACTION CODE	CURRENT	NEW	API NUMBER	WELL NAME	=		WELL	OCATION .			
	ENTITY NO.	ENTITY NO.			QQ	SC	TP	RG	000	SPUD	EFFECTIVI
B	20000	2900	1			<del>  ~</del>	<del>                                     </del>	I rec	COUNTY	DATE	DATE
	99999 COMMENTS:	200	43-047-33879	NBU #315	SENE	11	98	21B	Uintah	1/0 (1000)	
							<u> </u>	LAID	Cinian	4/26/2001	4/26/2001
Dang W	Bill Martin Air	TUB 8-2	7-01								
ACTION	CURRENT										
CODE	ENTITY NO.	NEW ENTITY NO.	API NUMBER	WELL NAME			WELL	OCATION		SPUD	FEEDAN
	20.00.	ENTITING.			QQ	SC	TP	RG	COUNTY	DATE	EFFECTIVE DATE
									500.1.1	MIL	DAIE
ELL 2 C	OMMENTS:							ļ		1	ļ
CTION	CURRENT	NEW	API NUMBER	WELL NAME					_		
CODE	ENTITY NO.	ENTITY NO.		TIELL MANNE	<u> </u>		METT TO			SPUID	EFFECTIVE
					QQ	SC	TP	RG	COUNTY	DATE	DATE
			j								
:TT 3 C	OMMENTS:									1	
CTION	Ollowar										
CODE	CURRENT ENTITY NO.	NEW ENTITY NO.	API NUMBER	WELL NAME			WELL LO	CATION			
	ENTITINO.	EMILLINO.			QQ	SC	TP	RG	COUNTY	SPUD DATE	EFFECTIVE
	ľ								COCKIT	- DATE	DATE
LL 4 CC	MMENTS:						- 1	1		ļ .	
										<u> </u>	
CTION	CURRENT	NEW	API NUMBER	WELL MANY			_				
ODE	ENTITY NO.	ENTITY NO.	THE THOMBEST	WELL NAME			WELLLO	CATION		SPUD	EFFECTIVE
			<del></del>		QQ	SC	TP	RG	COUNTY	DATE	DATE
		ľ	Ī			ľ					
⊥5 CC	MMENTS:										
							3				
			Pr	ost-it* Fax Note 7671 Date	# of pages		¬ ˙				
TON CO	ODES (See instr	actions on back o	of form)		page		┛┢				
A-E	stablish new eng	ty for new well (s	des formales	Will Manager	hers ( )	MON			J. [/	<i>b</i>	
B-A	dd new well to e	risting entity (gro	sin or imit men	o Dept. Ca.			7 i	(_	1 hud	diam in	
C-R	e-assion well fro	m one existing e	DELL'ED SECRETOR	hone # Phone #			┨∶	<u>~</u>	ignature		
D-R	e-assion well fro	m one existing e	ntile to a name i Fi	Eax #	3 1 1 2		<b>-</b> ∤				
E-0	ther (explain in o	omments section	ING TO G HEM.		See and		_	_	Regulatory	Analyst	08/27/01
E: Usa	COMMENT see	For in available and	ı) ıy each Action coue					Ti	ile		00/2//01 Pate
9)		ANT IN CYTHREIT AM	IY GRAN ACION COUR	was serecada.	00 <b>i</b>		•			•	
71				TO STATE BY BY	-v - r =			P	hone No.	(435) 504	

DIVISION OF OIL, GAS AND MINING

Form 3160-5 (August 1999)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135

	Expires: November 30, 2000
5.	Lease Serial No. U-0141317
	TCT-di- Allestee on Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					U-0141317  6. If Indian, Allottee or Tribe Name U & O	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No. NATURAL BUTTES UN	
1. Type of Well  ☐ Oil Well ☑ Gas Well ☐ Other					8. Well Name and No. NBU 315	
2. Name of Operator Contact: CHERYL CAMERO EL PASO PRODUCTION E-Mail: Cheryl.Ca				oastalCorp.c		
P O BOX 1148		3b. Phone No. (include area code) Ph: 435.781.7023 Fx: 435.789.4436		10. Field and Pool, or Exploratory NATURAL BUTTES		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  Sec 11 T9S R21E Mer SENE 1798FNL 770FEL					11. County or Parish, and State UINTAH COUNTY, UT	
12. CHECK APPR	OPRIATE BOX(ES) TO	INDICATE N	ATURE OF	NOTICE, RE	EPORT, OR OTHE	ER DATA
TYPE OF SUBMISSION TYPE OF ACTION						
☐ Notice of Intent  Subsequent Report	☐ Alter Casing		epen		<ul><li>□ Water Shut-Off</li><li>□ Well Integrity</li><li>☑ STARTUP</li></ul>	
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon ☐ Temporarily Abandon				
	☐ Convert to Injection ☐ Plug Back ☐ Water Dis		Pisposal			
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  The subject well was placed on sales 8/20/01. Refer to the attached Chronological History Report.  **RECEIVED**  SEP 0 4 2001						
DIVISION OF OIL, GAS AND MINING						
14. I hereby certify that the foregoing is true and correct.  Electronic Submission #6876 verified by the BLM Well Information System  For EL PASO PRODUCTION, sent to the Vernal						
Name (Printed/Typed) CHERYL CAMERON			Title OPERA	TIONS	- A- 4	
Signature huy Co	Date 08/30/2	001				
	THIS SPACE FO	OR FEDERAL	OR STATE	OFFICE U	SE	- Lucition and Allerton and
Approved By			Title		Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  Office						
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						

#### **EL PASO** PRODUCTION REPORT

#### CHRONOLOGICAL HISTORY

NBU 315 SESE SEC 11, T9S, R21E NATURAL BUTTES FIELD UINTAH COUNTY, UT

WI: 100% PBTD:

PERFS:

CSG:

SPUD DATE:

AFE DESCR., AFE: 053901

FORMATION: CWC(M\$):

DRILLING REPORT:

Natural Buttes, Uintah, UT Rig: CoastalDril 1 WI: 100% AFE: 053901 ATD: 6800'

DHC: xxx /CWC: xxx /DC: 29 /CC: 29 SD: 7/26/01 Target: Wasatch @ 4360'

" ക

95'/3 hrs MIRU. Drilling to present depth. TD: 140 MW: 8.5 7/26/01

Drilling to present depth. TD: 279 MW: 8.5 139'/4 hrs 7/27/01

POOH. Run & cement 8 5/8" surface casing. NU & test "A" section & BOP's.

1,610'/22.5 hrs Drilling to present depth. MW: 8.4 TD: 4,410 7/30/01

MW: 8.4 1,380'/23 hrs Drilling to present depth. TD: 5,790 7/31/01

TD: 6,740 MW: 8.6 950'/22.5 hrs Drilling to present depth. 8/1/01

Drilling to TD. Circulate bottoms 8/2/01 TD: 6,900 MW: 8.6 160'/3 hrs

up. Short trip - working tight hole.

W&R 6,745 - 6,900. TD: 6,900 MW: 8.6 160'/3 hrs 8/3/01

Circulate & condition mud. POOH to log. Tool sat down @ 5,314'. TIH w/ bit.

TD: 6,900 MW: 9.2 ND BOP's. NU & test tubing head. 8/6/01

Clean mud tanks. Rig released 8/5. Move to Gose Fed 3-18 today. Final report.

#### AFE# 053901

#### AFE DESCRIPTION: AFE, DRILL & COMPLETE WASATCH

8/15/01

PREP TO PERF

MIRU. PU & RIH W/2 3/8" TBG. TAG PBTD @ 6844'. PICKLE TBG W/3 BBLS 15% HCL.

POOH

8/16/01

PREP TO FRAC

PRESS TST 4 ½" CSG TO 5000#. HELD. ESTABLISH INJ RATE INTO 4 ½" X 8 5/8" ANNULUS @ 3 ½ BPM W/0 PRESS. PERF WASATCH 6792'-96', 4 SPF, 16 HOLES & 6782'-88', 4 SPF, 24 HOLES. 0 PRESS. BRK DN PERFS W/1700# @ 1 BPM. PUMP 20 BBLS 2%

KCL @ 3 1/2 BPM. ISIP: 600#, FG: 0.52.

8/17/01

PREP TO FRAC STAGES 4 & 5

STAGE 1: BRK DN PERFS 6782'-96' W/1700# @ 1 BPM, FG: 0.52. FRAC W/503 BBLS YF113ST LIQ GEL & 47000# 20/40 SD W/PROP NET IN LAST 10% SD. ISIP: 1480#, FG: 0.65, NET PRESS INC: 880#, MTP: 3050#, MTR: 35 BPM, ATP: 2500#, ATR: 30 BPM. RIH

W/CBP & PERF GUN. SET CBP @ 6700'.

STAGE 2: PERF WASATCH 6450'-54', 4 SPF, 16 HOLES. BRK DN W/1628# @ 2.7 BPM. ISIP: 711#, FG: 0.54. FRAC W/423 BBLS YF113ST LIQ GEL & 37,500# 20/40 SD W/PROP NET IN LAST 10% SD. ISIP: 1062#, FG: 0.60, NET PRESS INC: 351#, MTP: 3764#, ATP: 1725#, MTR: 25 BPM, ATR; 22.9 BPM. PU & RIH W/CBP & PERF GUN. SET CBP @ 6390'. UNABLE TO SHEAR OFF SETTING TOOL PULL OUT OF ROPE SOCKET. FISH PERF

**GUN & SETTING TOOL.** 

STAGE 3: PERF WASATCH 6314'-6324', 4 SPF, 40 HOLES. BRK DN W/1652# @ 2.2 BPM -ISIP: 890#, FG: 0.57. FRAC W/703 BBLS YF115ST LIQ GEL & 65,000# 20/40 SD W/PROP NET IN LAST 10% SD. ISIP: 1305#, FG: 0.64, NET PRESS INC: 415#, MTP: 3131#, ATP: 1880#, MTR: 32 BPM, ATR: 29.1 BPM. PU & RIH W/CBP & PERF GUN. SET CBP @ 6260'.

STAGE 4: PERF WASATCH 6156'-6166', 4 SPF, 40 HOLES. SDFN.

Page 1

#### 8/20/01 ON SALES

8/18/01 PROG: <u>STAGE 4</u>: PERF 6156'-66', 40 HOLES. BROKE PERFS @ 1780# @ 2.1 BPM. ISIP 950#, FG: 0.52. PUMPED 485 BBLS YF115ST W/43,500 LBS W/PROP NET. ISIP: 1770#, MTP: 2940#, MTR: 26.2 BPM. ATP: 2084#, ATR: 24.5 BPM, FG: 0.72, NPI: 820#. SET CBP @ 6100'. PERFED 6000'-6010', 40 HOLES. BROKE PERFS 2515# @ 2 BPM. ISIP: 1778#, FG: 0.73. PUMP 480 BBLS YF115ST W/47,060 LBS 20/40 SD W/PROP NET. ISIP: 1851#, MTP: 3014#, MTR: 23.8 BPM, ATP: 2044#, ATR: 23.8 BPM, FG: 0.74, NPI: 73#. SET CBP @ 5920'. RIH W/3 7/8" BIT, PUMP-0FF BIT SUB, 1 JT TBG & SN ON 2 3/8" TBG. DRILLED OUT CBP'S @ 5920', 6100', 6260', 6390' & 6700'. CLEANED OUT TO PBTD @ 6844'. PUH & LANDED TBG W/EOT @ 6753' & SN @ 6718'. ND BOP & NU TREE. DROPPED BALL & PUMPED OFF BIT. FLOWED OVERNIGHT CP: 1150#-1300#, TP: 650# TO 600#, CHK: 24/64", BWPH: 39-12, SD: LIGHT TO TRACE.

8/19/01 PROG: TURNED TO SALES. SPOT READING 1457 MCFD.

8/20/01 PROG: 1218 MCF, 73 BW, TP: 1650#, CP: 1650#, CHK: 16/64", 16 HRS, LP: 250#. TLTR: 2804 BBLS, TLR: 1140 BBLS, LLTR: 1664 BBLS.

#### 8/21/01 PROD TO SALES

1927 MCF, 0 BC, 67 BW, TP: 1308#, CP: 1518#, 16/64" CHK, 24 HRS, LP: 154#. TLTR: 2804 BBLS, TLR: 1207 BBLS, LLTR: 1597 BBLS.

#### 8/22/01 PROD TO SALES

1847 MCF, 0 BC, 61 BW, TP: 1254#, CP: 1467#, 16/64" CHK, 24 HRS, LP: 151#. TLTR: 2804 BBLS, TLR: 1268 BBLS, LLTR: 1536 BBLS.

#### 8/23/01 PROD TO SALES

1449 MCF, 0 BC, 20 BW, TP: 1729#, CP: 1734#, 16/64" CHK, 24 HRS, LP: 105#. TLTR: 2804 BBLS, TLR: 1288 BBLS, LLTR: 1516 BBLS.

#### 8/24/01 PROD TO SALES

196 MCF, 0 BC, 26 BW, TP: 1833#, CP: 1815#, 16/64" CHK, 6 HRS, LP: 110#. HI-LO VALVE CLOSED DUE TO CIG COMPRESSOR BEING DN. TLTR: 2804 BLS, TLR: 1314 BBLS, LLTR: 1490 BBLS.

#### 8/27/01 PROD TO SALES

8/25/01 PROG: FLWD 529 MCF, 0 BW, FTP: 1848#, CP: 1854#, 16/64" CHK, 18 HRS, LP: 107#, DN 6 HRS – SEPERATOR & FLOW LINE FROZE.
8/26/01 PROG: FLWD 84 MCF, 0 BW, FTP: 1848#, CP: 1854#, 16/64" CHK, 1 HR, LP: 106#, DN 23 HRS W/FROZEN SEPERATOR & FLOW LINE FREEZE.
8/27/01 PROG: FLOWED 1492 MCF, 5 BW, FTP: 1268#, CP: 1502#, 16/64" CHK, 17 HRS, LP: 164#. DN 7 HRS W/FROZEN SEPERATOR. TLTR: 2804 BBLS, TLR: 1319 BBLS, LLTR: 1485 BBLS. FINAL REPORT. IP DATE: 8/20/01 FLWG 1927 MCF, 67 BW, FTP: 1308#, CP: 1518#, 16/64" CHK, 24 HRS, LP: 154#.

Form \$160-4 (August 1999)

## UNI O STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

FORM APPROVED OMB NO. 1004-0137 Expires: November 30, 2000

5. Lease Serial No.

7.				
	 1_(	1	41	131

		03.37.11	I <b>∑</b> Ga		Dry (	Other					6. I	f Indian, Allo	tee or Tribe	Name
a. Type of W		Oil Well		- 4			<b>П</b> . вы	- Book	Diff.	Desur		Uinta	h & Oura	ıy
b. Type of Co	ompletion:	2	_	m W	ork Over	Deepen	☐ Plu	g Back	Ditt.		7. (	Jnit or CA Ag		
		0	ther									Natura	Buttes U	Jnit
2. Name of O	perator	<u>.,,</u> .								Ì	8. I	Lease Name a		
			El P	aso Pro	duction C	Company						Natural B	uttes Uni	t #315
3. Address							3a. Pho	ne No. (incl	ude area	code)	9	API Well No.		
	POI	Box 114	18 Verna	ıl. Utah	84078			(435)-78	31-702	3		43-0	47-33879	9
4. Location o	f Well (Rep	ort locatio	ns clearly	and in acc	ordance with	Federal requ	uirement	s)*			10	Field and Poo		
											10.		i Buttes l	
At surface			SENE	1798	FNL & 77	OFEL					11.	Sec., T., R., N		
At top prod.	interval reno	orted belov	w									Survey or Are	ea Sec.11	1-T9S-R21E
At top prod.	mervan repe	J. 100 00.0									12.	County or Par		13. State
At total dept	h											Uintah Co		Utah_
14. Date Spi		<del>\</del>	15. Da	te T.D. Re	ached	<u> </u>		e Complete	y V	lu to Drod	17.	Elevations (E		
•	04/26/01			0	8/05/01		4	D&A (		ly to Prod.		4849.2'	Ungrade	d GL
				In Di	a Pagle T.D.	: MD	1	00/2		20. Depth	Bridge	Plug Set: MI	5	
18. Total De	epth: MD TVD	) F	900'	19. PIL	ig Back T.D.	TVD	6844'	•				TV	/D	
21. Type El	actric & Oth	or Mecha	nical Logs	Run (Subn	nit copy of ea	nch)			22. Was	well cored	? 🔕 N		s (Submit co	
MCTICA	VIGALL	26-8	-21-01					1		DST run?			s (Submit co	
UIT-CBL	GR - 9	-21-01	DST	1cul	R-8-2	1-01, UI	T_CISI	1-6-8-80	Dire	ctional Sur	vey? [2	No 🚨	Yes (Subm	it copy)
23. Casing	and Liner Re	ecord (Re	port all stri	ings set in	well)									
				(MD)	Bottom (MI	Stage Co	ementer	No. of S		Slurry V	1	Cement Top	)* A1	mount Pulled
Hole Size		Wt. (#/ft	.) 10	(IVID)		De <sub>l</sub>	oth.	Type of C		(BBL	<del>}  </del> -			
12 1/4"	8 5/8"	24#			275'		155				Surface	_		
7 7/8"	4 1/2"	11.6#			6888'		1218				Surface			
								ļ					_	
								<u>L</u>		L				
24. Tubing		(A/D) [	Dagles De-	th (MD)	Size	Denth S	et (MD)	Packer Der	oth (MD)	Siz	ze	Depth Se	t (MD)	Packer Set (MD)
Size	Depth Set	· ( · · · · · · · · · · · · · · · · · ·	Packer Dep	th (MD)	Size	Deptil 3	ct (IVID)	Tacker Be	per (1.12)			1 '		
2 3/8"	675							<del>                                     </del>						
25. Produc	ing Intervals	L				26. Per	foration l	Record		•				
23. Floduc	Formation			Тор	Bottom	P	erforated	Interval		Size	N	o. Holes	Perf	f. Status
Pofor to	the addition					Refer t	o the ad	ditional pag	je					
	Jule addition	orial page	<u> </u>											
<u>B)</u>			<del></del>											
<u>C)</u> D)												RE		VFD_
27. Acid. I	racture, Tre	atment, C	ement Sque	eeze, Etc.								- 1 House 1		<b>V i i i i</b>
	Depth Inter							Amount an	d type of	Material			<del> </del>	nne
Refer to	the addit	ional pa	age									30	P 24 2	.001
<del></del>													VISION	<u> </u>
														MINING
									····			<del></del>	10 7010	WIII VII VO
	ction - Interv			los	16	Water	Oil Gr	avity	Gas		Produ	ction Method		
Date First	Test	Hours Tested		Oil BBL	Gas MCF	BBL	Corr. A	•	Gravity		1			
Produced 08/20/01	Date 08/20/01	1	- Todaction	0	1,927	67		0	<u></u>	0			Flowing	
Choke	Tbg. Press.	Csg.	24 Hr.	Oil	Gas	Water	Oil Gr	-	Well Star	tus				
Size	Flwg.	Press.	Rate	BBL		BBL	Соп. /		İ			Producir	na	
16/64		1518#		0	1927	67		0 .	<u> </u>			1 100001	<u>'8</u>	
	uction - Inte		T <sub>em</sub>	Tön	Ica	Water	Oil Gr	ravity	Gas	<del> </del>	Prod	uction Method		
Date First	Test	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Corr.	•	Gravity					
Produced	Date	1 ezien	- Todacion											
Choke	Tbg. Press.	Csg.	24 Hr.	Oil	Gas	Water		ravity	Well Sta	tus				
Size	Flwg.	Press.	Rate	BBL	MCF	BBL	Corr.	API						
	SI	<u></u>		<u> </u>		l	l		<u>.l</u>					
(See instri	uctions and	spaces for	· additional	data on re	everse side)									

•				_								
28h Proc	duction - Inte	erval C				· · · · · · · · · · · · · · · · · · ·						
Date First		Hours	Test	Oil	Gas	Water	Oil Gravity	Gas Gravity	Production Method			
roduced	Date	Tested	Production	BBL	MCF	BBL	Сопт. АРІ					
Choke	Tbg. Press.	Csg.	24 Hr.	Oil	Gas	Water	Gas : Oil	Well Status	<u> </u>			
Jnoke Size	Flwg.	Press.	Rate	BBL	MCF	BBL	Ratio					
	SI	1	<b>→</b>									
28c. Pro	duction - Inte	erval D						10 0 1	D. J. S. Maked			
Date First		Hours	Test	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method			
Produced	Date	Tested	Production	BBL	INICI	BBL						
Choke	Tbg. Press.	Csg.	24 Hr.	Oil	Gas	Water	Gas : Oil	Well Status				
Size	Flwg.	Press.	Rate	BBL	MCF	BBL	Ratio					
	SI		<b>→</b>	İ								
	osition of G	as (Sold, us	sed for fuel,	vented, etc	.)							
Sold	mary of Pore	70000	(Include Act	ifore):				31. Formati	on (Log) Markers			
								3	J. (2-5)			
Sho	w all importa	ant zones o	f porosity an	d contents	thereof: Cor	ed intervals at	nd all drill-stem					
tests	s, including d	lepth interv	al tested, cu	shion used	l, time tool op	en, flowing and	d shut-in pressures	•				
and	recoveries.							İ				
				T-		· .: C			Name	Тор		
Formation Top Bottom Descriptions, Contents, etc.						ils, etc.		TVAITO	Meas. Depth			
Green	River	1850'	5271'					ļ				
Wasa		5271'										
										1		
			•					1				
							•					
		1					,	Ì				
		i		1				ĺ		1		
			1			-		1				
			1									
			Ì					ļ				
								]				
								Ì				
		İ						ļ		l		
								ļ				
		Ì		-				İ	DEA			
		Ì	]					RECEIVED				
32. Ad	lditional rem	arks (inclu	de plugging	procedure	):		-		<b>8</b>			
									SEP :	2 4 2001		
									DIVAC	ION OF		
										ION OF		
									OIL, GAS /	AND MINING		
33. Ci	rcle enclosed	d attachmer	nts:									
	Electrical/M			set req'd.)		2. Geologic F	•	DST Report	4. Directional Surve	у		
5.	Sundry Not	ice for plug	gging and ce	ment verif	ication	5. Core Analy	ysis 7.	Other:				
								1.0 11 17	11 de (ees etteched	instructions)*		
36. I h	ereby certify	that the fo	regoing and	attached is	nformation is	complete and c	correct as determin	ed from all avails	able records (see attached	msu ucuons)		
									1.t A alvad			
Na	me (please p	orint) <u>C</u> h	eryl Cam	eron			Title	Sr. Reg	ulatory Analyst			
	10	<u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>	$\sim$	$\mathbf{\hat{a}}$								
Sic	gnature D	المراكب الم	Lucu	2im			Date	9/20/01				
								-l., and:116.11	to make to any denortmen	t or agency of the Unite		
Title 1	8 U.S.C. Sec	ction 1001 a	ind Title 43 U	J.S.C. Sect	ion 1212, mak or representati	e it a crime for ons as to any r	any person knowin natter within its ju	risdiction.	to make to any departmen			
States	any talse, th	cutious of	nauouicnt s	MICHIGINS	or representati					0. 000, 4000 572		

o U.S. GPO: 1999-573-624

#### Form 3160-4 Additional Page For Comments

## WELL COMPLETION OR RECOMPLETION REPORT AND LOG

<u>U-0141317</u>

Lease Serial No.

NBU#315

**SE/NE SEC. 11,T9S, R21E** 

ITEM# 25, 26 & 27

INTERVAL	SIZE	NUMBER
WASATCH 6792'-6796' 6782'-6788' 6450'-6454 6314'-6324' 6156'-6166' 6000'-6010'	4 SPF 4 SPF 4 SPF 4 SPF 4 SPF	16 HOLES 24 HOLES 16 HOLES 40 HOLES 40 HOLES 40 HOLES
DEPTH INTERVAL	MOUNT & KI	IND OF MATERIAL
6782-6796' 6450'-6454' 6314'-6324' 6156'-6166' 6000'-6010'	423 BBLS YF1 703 BBLS YF1 485 BBLS YF1	13ST LIQ GEL & 47000# 20/40 SD W/PROP 13ST LIQ GEL & 37500# 20/40 SD W/PROP 15ST LIQ GEL & 65000# 20/40 SD W/PROP 15ST W/43500# PROP NET 115ST W/47060# 20/40 SD W/PROP NET

JAN. 17. 2003 3:34PM

TPORT

NO. 173 P. 2



### WESTPORT OIL AND GAS COMPANY, L.P.

410 Seventeenth Street #2300 Deriver Colorado 80202-4436 Telephonet 303 573 5404 Fast: 303 573 5609

February 1, 2002

Department of the Interior
Bureau of Land Management
2850 Youngfield Street
Lakewood, CO 80215-7093
Attention: Ms. Martha Maxwell

RE: BLM Bond CO-1203

BLM Nationwide Bond 158626364

Surety - Continental Casualty Company

Belco Energy Corporation merger into Westport Oil and Gas Company, Inc.

Conversion of Westport Oil and Gas Company, Inc., into Westport Oil and Gas Company, L.P.

Assumption Rider - Westport Oil and Gas Company, L.P.

#### Dear Ms. Maxwell:

Pursuant to our recent conversations, please find the following list of enclosures for the BLM's consideration and approval:

Two (2) Assumption Riders, fully executed originals.

Copies of Belco Energy Corporation merger into Westport Oil and Gas Company, Inc. Copies of Westport Oil and Gas Company, Inc., conversion into Westport Oil and Gas Company, L.P.

List of all Federal/BIA/State Leases - Beloo/Westport's leases - in all states.

Please inform us of any additional information needed to complete the change to Westport Oil and Gas Company, L.P., as operator of record.

I thank you for your assistance and cooperation in this matter. Please do not hesitate contacting the undersigned, should a question arise.

Sincerely,

Westport Oil and Gas Company, L.P.

Black

Debby J. Black Engineer Technician

Encl:



## United States Department of the Interior RECEIVED

#### **BUREAU OF LAND MANAGEMENT**

FEB 2 2 2002

Utah State Office P.O. Box 45155 Salt Lake City, UT 84145-0155

DIVISION OF OIL. GAS AND MINING

In Reply Refer To: 3106 UTU-25566 et al (UT-924)

FEB 2 1 2002

#### **NOTICE**

Westport Oil and Gas Company L.P.

Oil and Gas

410 Seventeenth Street, #2300

:

Denver Colorado 80215-7093

Acceptable evidence has been received in this office concerning the name change of <u>Westport Oil</u> and <u>Gas Company, Inc.</u> into <u>Westport Oil and Gas Company, L.P.</u> with <u>Westport Oil and Gas Company, L.P.</u> being the surviving entity.

Name Change Recognized

For our purposes, the name change is recognized effective December 31, 2001.

The oil and gas lease files identified have been noted as to the name change. The exhibit was compiled from a list of leases obtained from our computer program. We have not abstracted the lease files to determine if the entities affected by this name change hold an interest in the leases identified nor have we attempted to identify leases where the entities are the operator on the ground maintaining no vested recorded title or operating rights interests. We will be notifying the Minerals Management Service and all applicable Bureau of Land Management offices of the change by a copy of this notice. If additional documentation for changes of operator are required by our Field Offices, you will be contacted by them.

If you identify additional leases in which the entities maintain an interest, please contact this office and we will appropriately document those files with a copy of this Notice.

Due to the name change, the name of the principal/obligor on the bond is required to be changed from Westport Oil and Gas Company, Inc. to Westport Oil and Gas Company, L.P.. You may accomplish this either by consent of surety rider on the original bond or a rider to the original bond. The bonds are held in Colorado.

UTU-03405 UTU-20895 UTU-25566 UTU-43156 UTU-49518 UTU-49519 UTU-49522 UTU-49523

> Robert Lopez Chief, Branca of Minerals Adjudication

cc: Moab Field Office

Vernal Field Office

MMS, Reference Data Branch, MS3130, PO Box 5860, Denver CO 80217 State of Utah, DOGM, Attn: Jim Thompson (Ste. 1210), Box 145801, SLC UT 84114

Teresa Thompson (UT-922) Joe Incardine (UT-921)

#### UNITED STATES GOVERNMENT

## memorandu

Branch of Real Estate Services Uintah & Ouray Agency

۰,

Date:

5 December, 2002

Reply to

Supervisory Petroleum Engineer

Subject:

Modification of Utah Division of Oil, Gas and Mining Regulations

To

Director, Utah Division of Oil, Gas and Mining Division: John Baza

We have been advised of changes occurring with the operation of your database for Change of Operator. You will be modifying your records to reflect Change of Operator once you have received all necessary documentation from the companies involved, and perhaps in advance of our Notice of Concurrence/Approval of Change of Operator where Indian leases are involved.

We have no objection.

With further comment to Rulemaking, I wish to comment concerning the provision of Exhibits for upcoming Hearings. I would like to see the Uintah & Ouray Agency, BIA, and the Ute Indian Tribe, Energy & Mineral Resources Department added to the list of those parties that receive advance Exhibits so as to allow us to have research time prior to Hearing dates. We will be able to provide a more informed recommendation to the Oil, Gas and Mining Board. It would be best if we would receive only those Exhibits that concern Indian lands, specifically on or adjacent to Indian lands. This may be a difficult situation to attain, as it is not always clear where 'on or adjacent' occurs.

I am aware that you have gone to extra effort to correct this matter already, and I fully appreciate it. My request is intended only to allow the addition of Uintah & Ouray Agency and Ute Indian Tribe to the official listing.

We appreciate you concern, and hope that these comments are timely enough for consideration in the revision process. liales H Common

CC:

Minerals & Mining Section of RES

Ute Energy & Mineral Resources Department: Executive Director

chrono



## United States Department of the Interior

BUREAU OF INDIAN AFFAIRS
Washington, D.C. 20240
FEB 1 0 2003

Carroll A. Wilson Principal Landman Westport Oil and Gas Company, L.P. 1368 South 1200 East Vernal, Utah 84078

Dear Mr. Wilson:

This is in response to your request for approval of RLI Insurance Company's Nationwide Oil and Gas Lease Bond No. RLB0005239 executed effective December 17, 2002, (\$150,000 coverage) with Westport Oil and Gas Company, L. P., as principal.

This bond is hereby approved as of the date of this correspondence and will be retained in the Bureau of Indian Affairs' Division of Real Estate Services, 1849 C Street, NW, MS-4512-MIB, Washington, D.C. 20240. All Bureau oil and gas regional offices and the surety are being informed of this action.

In cases where you have existing individual and/or collective bonds on file with one or more of our regional offices, you may now request those offices, directly, to terminate in lieu of coverage under this Nationwide Bond.

Enclosed is a copy of the approved bond for your files. If we may be of further assistance in this matter, please advise.

Sincerely,

ACTING

Director, Office of Trust Responsibilities

**Enclosure** 



## United States Department of the Interior

#### **BUREAU OF LAND MANAGEMENT**

Utah State Office P.O. Box 45155 Salt Lake City, UT 84145-0155

IN REPLY REFER TO UT-922

February 27, 2003

Westport Oil and Gas Company, L.P. Attn: Gary D. Williamson 1670 Broadway, Suite 2800 Denver, Colorado 80202

Re:

Natural Buttes Unit Uintah County, Utah

#### Gentlemen:

On February 27, 2003, we received an indenture dated December 17, 2002, whereby El Paso Production Oil & Gas Company resigned as Unit Operator and Westport Oil and Gas Company, L.P., was designated as Successor Unit Operator for the Natural Buttes Unit, Uintah County, Utah.

This indenture was executed by all required parties and the signatory parties have complied with Sections 5 and 6 of the unit agreement. The instrument is hereby approved effective February 27, 2003. In approving this designation, the Authorized Officer neither warrants nor certifies that the designated party has obtained all required approval that would entitle it to conduct operations under the Natural Buttes Unit Agreement.

Your nationwide (Colorado) oil and gas bond No. 1203 will be used to cover all operations within the Natural Buttes Unit.

It is requested that you notify all interested parties of the change in unit operator. Copies of the approved instruments are being distributed to the appropriate federal offices, with one copy returned herewith.

Sincerely,

/s/ Robert A. Henricks

Robert A. Henricks Chief, Branch of Fluid Minerals

#### Enclosure

bcc:

Field Manager - Vernal (w/enclosure)

SITLA

Division of Oil, Gas & Mining Minerals Adjudication Group

File - Natural Buttes Unit (w/enclosure)

Agr. Sec. Chron

Fluid Chron

UT922:TAThompson:tt:02/27/2003

**RECEIVED** 

FEB 2 8 2003

DIV. OF OIL, GAS & MINING

### STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

	DIVISION OF OIL, GAS AND MIN	NING	5. LEASE DESIGNATION AND SERIAL NUMBER:
SUNDRY	NOTICES AND REPORTS	S ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
	the size for the decree existing wells below current	cost bottom hole depth, reenter nivened wells, or to	7. UNIT or CA AGREEMENT NAME:
Do not use this form for proposals to drill no drill horizontal la	ew wells, significantly deepen existing wells below curr terals. Use APPLICATION FOR PERMIT TO DRILL fo	orm for such proposals.	
1. TYPE OF WELL OIL WELL	GAS WELL OTHER_		8. WELL NAME and NUMBER: Exhibit "A"
2. NAME OF OPERATOR:			9. API NUMBER:
	Production Oil & Gas Company		40 SISI D AND DOOL OF WILLDOAT
3. ADDRESS OF OPERATOR:  9 Greenway Plaza	Houston STATE TX	77064-0995 (832) 676-5933	10. FIELD AND POOL, OR WILDCAT:
4. LOCATION OF WELL			
FOOTAGES AT SURFACE:			COUNTY:
QTR/QTR, SECTION, TOWNSHIP, RAN	GE, MERIDIAN:		STATE:
			UTAH
11. CHECK APP	ROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
NOTICE OF INTENT	ACIDIZE	DEEPEN	REPERFORATE CURRENT FORMATION
(Submit in Duplicate)	ALTER CASING	FRACTURE TREAT	SIDETRACK TO REPAIR WELL
Approximate date work will start:	CASING REPAIR	NEW CONSTRUCTION	TEMPORARILY ABANDON
<u>.</u> .	CHANGE TO PREVIOUS PLANS	OPERATOR CHANGE	TUBING REPAIR
	CHANGE TUBING	PLUG AND ABANDON	VENT OR FLARE
SUBSEQUENT REPORT (Submit Original Form Only)	CHANGE WELL NAME	PLUG BACK	WATER DISPOSAL
Date of work completion:	CHANGE WELL STATUS	PRODUCTION (START/RESUME)	WATER SHUT-OFF
	COMMINGLE PRODUCING FORMATIONS	RECLAMATION OF WELL SITE	OTHER:
	CONVERT WELL TYPE	RECOMPLETE - DIFFERENT FORMATION	
12. DESCRIBE PROPOSED OR CO		pertinent details including dates, depths, volur	nes, etc.
Operator change to V effective December 1	OMPLETED OPERATIONS. Clearly show all possible of the company of t		nes, etc. 2800, Denver, CO. 80202-4800,
Operator change to Vertice of the operator of	DMPLETED OPERATIONS. Clearly show all possible of the company of t	, L.P., 1670 Broadway, Suite 2	
Operator change to Vertective December 1	Vestport Oil and Gas Company 7, 2002.	, L.P., 1670 Broadway, Suite 2	2800, Denver, CO. 80202-4800,
Operator change to Vertice of the operator of	DMPLETED OPERATIONS. Clearly show all possible of the company of t	, L.P., 1670 Broadway, Suite 2	
Operator change to Verificative December 1  BOND#State S	Vestport Oil and Gas Company 7, 2002.	, L.P., 1670 Broadway, Suite 2	2800, Denver, CO. 80202-4800,
Operator change to Vertective December 1  BOND#State S	Vestport Oil and Gas Company 7, 2002.  urety Bond No. RLBG Fee Bond No. RLBG	, L.P., 1670 Broadway, Suite 2	RECEIVED FEB 2 8 2003
Operator change to Verificative December 1  BOND #	Vestport Oil and Gas Company 7, 2002.  Urety Bond No. RLBC Fee Bond No. RLBC ON OIL & GAS COMPANY	, L.P., 1670 Broadway, Suite 2	RECEIVED
Operator change to Verificative December 1  BOND #	DMPLETED OPERATIONS. Clearly show all possible of the company of t	, L.P., 1670 Broadway, Suite 2	RECEIVED FEB 2 8 2003 DIV. OF OIL, GAS & MINING
Operator change to Verificative December 1  BOND #	DMPLETED OPERATIONS. Clearly show all possible of the company of t	, L.P., 1670 Broadway, Suite 2	RECEIVED FEB 2 8 2003 DIV. OF OIL, GAS & MINING

Form 3 160-; (August 199	9)	UNITED STATES	S NTERIOR		PORM APPROVED CNO No. 1004-0135	
	BUI	RBAU OF LAND MANA	AGEMENT		Bepires Incommer 30, 2000  5. Loase Serial No.	
	SUNDRY	Y NOTICES AND REPOR	RTS ON WELLS		SEE ATTACHED EXHIBIT "A"	
	abandoned well	is form for proposals ( i. Use Form 3160-3 (API	to drill or reenter an D) for such proposals.		6. If Indian, Allottee or Tribe Name	
		LICATE - Other instr	uctions on reverse sk	de	7. If Unit or CA/Agreement, Name and/or No	
1. Type of Oil		Other		-		
	Operator				8. Well Name and No.	_
WESTPO	RT OIL & GAS CO	OMPANY, L.P.			SEE ATTACHED EXHIBIT "A"	_
			3b. Phone No. (include are	a code)	SEE ATTACHED EXHIBIT "A"	
4. Location	1148 VERNAL, U	JT 84078 T., R., M., or Survey Descripti	(435) 781-7023		10. Field and Pool, or Exploratory Area	
		1., K., M., or Survey Descripit	on)			
SEE ATTA	CHED EXHIBIT	"A"			11. County or Parish, State	_
					UINTAH COUNTY, UT	
	12. CHECK APP	ROPRIATE BOX(ES) TO	INDICATE NATURE OF N	OTICE RI	EPORT, OR OTHER DATA	_
TYPEO	P Submission		ACTION		_	
Notice of	Intent	☐ Acidize				-
		Aiter Casing	I I 🐃	Production ( Reclamation	(Start/Resume) Water Shut-Off	
Zaptedne	nt Report	Casing Repair		Recomplete	Acu michità	
Final Aba	indonment Notice	Change Plans Convert to Injection	Plug and Abendon :	Temporarily	Abandon SUCCESSOR OF	-
13. Describe Pr	oposed or Completed O			Water Dispo	<u> </u>	<i>-</i> -
following e	mnjetion of the involve	work will be bettormed or pro	wide the Bond No. on file with	BLM/RYA	late of any proposed work and approximate durat land true vertical depths of all pertinent markers Required subsequent reports shall be filed with pletion in a new interval, a Form 3160-4 shall be ng reclamation, have been completed, and the o	and zc
WESTPORT	OIL & GAS COMPA	ANY I D 18 CONCIDED	)ED =4 == -			
LANDS AND	IS RESPONSIBLE	UNDER THE TERMS AN	VD CONDITIONS OF THE	OR ON T	HE ATTACHED DESCRIBED	
CONDUCTE	D ON THE LEASED	LANDS OR PORTIONS	THEREOF, BOND COVE	ELEASE F	FOR THE OPERATIONS OR THIS WELL IS PROVIDED	
BY FEDERAL	L NATIONWIDE BO	)ND NO. 158626364, EFF	FECTIVE FEBRUARY 1, 2	ENAGE FL	ORIA MATIONNAME	
BOND NO. K	LB0005239, EFFE(	CTIVE FEBRUARY 10, 20	003.		A PIN IAN I IOMANDE	
	! :				RECEIVED	
					MAR 0 4 2003	
4. I hereby cor	tify that the foregoing is	s true and correct	-		DIV. OF GIL. CAC & MININ	G
Name (Print	CAMERON		Title		,	
Signature			OPERATIONS Date			
my	U amer		March 4, 2003			
pproved by		THIS SPACE F	OR FEDERAL OR STATE U	SE		
			Title		Date	
onditions of approveries that the application would entitle	val, if any, are attached. And cant holds legal or equitable the applicant to conduct open	peroval of this notice does not warr to thise to those rights in the subject	ant or Office			
itle 18 U.S.C. S	ection 1001 make it a	CONTRACTOR INCOME.			ent or agency of the United States any	
esc, nathious or	fraudulent statements (	or representations as to any ma	atter within its jurisdiction.	my departm	ent or agency of the United States any	

#### **OPERATOR CHANGE WORKSHEET**

ROUTING
1. GLH
2. CDW
3. FILE

### X Change of Operator (Well Sold)

The operator of the well(s) listed below has changed, effective:

Designation of Agent/Operator

Operator Name Change

Merger

12-17-02

FROM: (Old Operator):		<b>TO:</b> ( New Or	perator):		TO: ( New Operator):									
EL PASO PRODUCTION OIL & GAS COMPANY	1	WESTPORT C	IL & GAS	COMPANY	LP									
Address: 9 GREENWAY PLAZA		Address: P O B	OX 1148											
HOUSTON, TX 77064-0995	4	VERNAL, UT	84078											
Phone: 1-(832)-676-5933	-	Phone: 1-(435)-781-7023												
Account No. N1845	┪	Account No. N2115												
CA No		Unit: NATURAL BUTTES												
	•	Unit:	NATURA	LBUITES										
WELL(S)	Tana avenu	T. 22 222	T	IT ELACE	INTERNAL T	INVERT								
	SEC TWN RNG	API NO	ENTITY NO	TYPE	WELL	WELL STATUS								
NAME		43-047-33879		FEDERAL		P								
NBU 315				FEDERAL		P								
NBU 316		43-047-34413		FEDERAL		P								
NBU 400-11E		43-047-32544				P								
NBU 195		43-047-32355		FEDERAL FEDERAL		P								
NBU 182		43-047-32162				P								
NBU 174		43-047-32193		FEDERAL		P								
NBU 297		43-047-33040		FEDERAL										
NBU 56-11B		43-047-30480		FEDERAL		PA								
NBU 56-12B		43-047-30464		FEDERAL		P								
NBU 63N3		43-047-31097		FEDERAL		P								
NBU 375		43-047-34440		FEDERAL		APD								
NBU 376		43-047-34441		FEDERAL		APD								
NBU 418		43-047-34777		FEDERAL		APD								
CIGE 61-13-9-21		43-047-30550		FEDERAL		P								
CIGE 125-13-9-21		43-047-32084		FEDERAL		P								
CIGE 126-13-9-21		43-047-32087		FEDERAL		PA								
NBU 121	13-09S-21E	43-047-32086	2900	FEDERAL		P								
NBU 122		43-047-32303		FEDERAL		P								
CIGE 111D-13-9-21		43-047-32305		FEDERAL		P								
CIGE 214-13-9-21	13-09S-21E	43-047-32918	2900	FEDERAL	GW	P								
OPERATOR CHANGES DOCUMENTATION Enter date after each listed item is completed  1. (R649-8-10) Sundry or legal documentation was received	i from the FOI	RMER operator	on:	02/28/2003	<u>3</u> _									
<ul><li>2. (R649-8-10) Sundry or legal documentation was received</li><li>3. The new company has been checked through the Departs</li></ul>			03/04/200	_	oase on:	03/06/2003								
<ul><li>3. The new company has been checked through the Departs</li><li>4. Is the new operator registered in the State of Utah:</li></ul>	YES	_Business Num		1355743-01										
5. If NO, the operator was contacted contacted on:		_												

6. (1	2649-9-2)Waste Management Plan has been received on:	IN PLACE	
7.	Federal and Indian Lease Wells: The BLM and or operator change for all wells listed on Federal or Indian		
8.	Federal and Indian Units: The BLM or BIA has approved the successor of unit open	erator for wells listed on:	02/27/2003
9.	Federal and Indian Communization Agreem The BLM or BIA has approved the operator for all wells	ents ("CA"): s listed within a CA on:	N/A
10.	Underground Injection Control ("UIC") for the enhanced/secondary recovery unit/project for the		i UIC Form 5, Transfer of Authority to Inject, on:  N/A
<b>D</b> A	TA ENTRY: Changes entered in the Oil and Gas Database on:	03/11/2003	
2.	Changes have been entered on the Monthly Operator Ch	nange Spread Sheet on:	03/11/2003
3.	Bond information entered in RBDMS on:	N/A	
4.	Fee wells attached to bond in RBDMS on:	N/A	
<b>ST</b> 1.	ATE WELL(S) BOND VERIFICATION: State well(s) covered by Bond Number:	RLB 0005236	
<b>FE</b>	<b>DERAL WELL(S) BOND VERIFICATION:</b> Federal well(s) covered by Bond Number:	158626364	
IN 1.	DIAN WELL(S) BOND VERIFICATION: Indian well(s) covered by Bond Number:	RLB 0005239	
	E WELL(S) BOND VERIFICATION: (R649-3-1) The NEW operator of any fee well(s) listed or	overed by Bond Number	RLB 0005238
2.	The <b>FORMER</b> operator has requested a release of liability The Division sent response by letter on:	y from their bond on: N/A	N/A
LI 3.	CASE INTEREST OWNER NOTIFICATION (R649-2-10) The FORMER operator of the fee wells has of their responsibility to notify all interest owners of this continuous contractions.	been contacted and informe	d by a letter from the Division
CC	MMENTS:		
		<u> </u>	
_			

Form 3160-5 (August 1999)

## UNIT STATES DEPARTMENT OF THE INTERIOR DUBBALLOE LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires Inovember 30, 2000

. BUR	EAU OF LAND MANAG	EMENI	,		5. Lease Serial No.					
SUNDRY	NOTICES AND REPORTS	S ON WE	LLS		Multiple We	lls - se	e attached			
	s form for proposals to . Use Form 3160-3 (APD)				6. If Indian, A	lottee o	r Tribe Name			
	CATE – Other instru	ctions o	n reverse	side	7. If Unit or C.	_	ement, Name and/or No.			
1. Type of Well Oil Well Gas Well	Other				8. Well Name	and No.				
2. Name of Operator					Multiple We		e attached			
WESTPORT OIL & GAS COM	PANY, L.P.				9. API Well N					
3a. Address	7		e No. (include	area code)	Multiple We					
P.O. BOX 1148 VERNAL, UT 8		(435) 78	81-				Exploratory Area			
4. Location of Well (Footage, Sec., T.,	R., M., or Survey Description)				Natural Butt					
Multiple Wells - see attached					11. County or F	arish, S	tate			
	مو 									
12. CHECK A	APPROPRIATE BOX(ES) TO	INDICAT	E NATURE	OF NOTICE, R	EPORT, OR OT	HER D	ATA			
TYPE OF SUBMISSION			TY	PE OF ACTIO	N					
Notice of Intent	☐ Acidize	Deepe	en	Production	(Start/Resume)		Water Shut-Off			
Nouse of many	Alter Casing		ire Treat	Reclamati		□ ′	Well Integrity			
Subsequent Report	Casing Repair	New (	Construction	Recomple	te		Other			
_	Change Plans	= -	and Abandon	= :	ly Abandon	_				
Final Abandonment Notice	Convert to Injection	Plug		Water Dis						
13. Describe Proposed or Completed Ope If the proposal is to deepen directions Attach the Bond under which the wo following completion of the involved testing has been completed. Final A determined that the site is ready for fin Westport Oil & Gas requests a variance with a pressure-vacuum thief hatch ar condensate will not payout the increment	ally or recomplete horizontally, g rk will be performed or provide operations. If the operation rest bandonment Notices shall be file all inspection.  ce to Onshore Order No. 4, Pa nd/or vent line valve. The varia	the Bond Nults in a muled only after a muled only after art IIIC.a. reance is required.	ce locations an o. on file with tiple completion or all requireme quiring each s ested as an e	d measured and t BLM/BIA. Req n or recompletion nts, including rec cales tank be eq conomic analys	nue vertical depths uired subsequent re in a new interval ilamation, have bed uipped is shows the valu	of all perports should be a Former comp	ertinent markers and zones.  all be filed within 30 days a 3160-4 shall be filed once eleted, and the operator has a shrunk			
The volume lost to shrinkage by dropp	ping the tank pressure from 6	ozs. to 0 ps	ig is shown to	be 0.3% of the	tank volume. Thi	s was d	etermined by lab analysis			
of a representative sample from the fi										
The average NBU well produces appr							•			
month lost volume due to shrinkage.										
and maintaining the valves and other										
Westport Oil & gas requests approval		rease the v	alue of the we	ell to the operato	er and the minera	royalty	owners.			
14. I hereby certify that the foregoing is	true and correct						SEP 1 n 2002			
Name (Printed/Typed)	COPY SENT TO OP	Title		Ope	erations Mana	ger	SEP 1 11 2003			
J.T. Conley Signature	Initials: CH	Date	9	-2-200			IV. OF OIL GAS & MILITA			
- A CIVIC	THIS SPA	CE FOR FI	DERAL OR	PTATE LIGE		2				
Approved by			A A	<del>000bran n</del>	y ma	i	Federal Approval Of Thi			
			ل الاهــــــــــــــــــــــــــــــــــ	Itah Division Gas and	Mining	я. * 1:	Action is Necessary			
Conditions of approval, if any, are attached	Approval of this notice does not	warrant or	Office Off			E .				
certify that the applicant holds legal or equ which would entitle the applicant to condu	ct operations thereon.	wject least	Date:	7/16/05	- $ +$	<u> </u>				

Title 18 U.S.C. Section 1001, make it a crime for any person knowingly and militudy to make to any department of precious of the United States any false, fictitious or fraudulent statements or representations as to any matter within its juris licaon.

17はし 400	40-8-4   OEINE	UU00/U	AUUEQUUI EQ	43047330090031
NBU 261	30-9 21 SENW	UTU0581	891008900^	430473292800S1 V
NBU 262	33-£ NENE	UTU0576	8910089(	430473292900S1
NBU 263	34-9-21 SENW	U01194	891008900A	430473279300S1 ✓
NBU 264	1-10-21 SESW	U02842B	891008900A	430473300000S1
	2-10-21 NESE	ML13826	891008900A	430473279600S1 ✓
NBU 265				
NBU 266	10-10-21 SWNW	UTU0149079	891008900A	430473294100S1
NBU 267	10-10-21 NESW	UTU01416A	891008900A	430473294200S1
NBU 268	11-10-21 NENE	U01190	891008900A	430473300100S1
NBU 269	12-10-21 SWNW	UTU1196D	891008900A	430473347300S1
NBU 270 ,	13-10-21 SWNW	ML23608	891008900A	430473286200S1 🗸
NBU 271	24-10-20 SWNW	UTU4485	891008900A	430473288700S1
NBU 272	11-10-22 SWNE	U01197A	891008900A	430473288900S1 ✓
NBU 273	22-9-21 NWNW	UTU0147566	891008900A	430473290600S1
NBU 274	23-9-21 NESW	UTU149075	891008900A	430473290700S1
NBU 275	9-9-21 NWSW	UTU01188	891008900A	430473290500S1
NBU 277	19-9-22 SENE	UTU0284	891008900A	430473304200S1
NBU 278	30-9-22 SWSW	U463	891008900A	430473301100S1
NBU 280	31-9-22 NESW	ML22935A	891008900A	430473286500S1 ✓
NBU 281	32-9-22 SWSW	ML22649	891008900A	430473286600S1 ✓
NBU 282	32-9-22 NESE	ML22649	891008900A	430473286700S1
	3-10-22 NWNW	UTU01191	891008900A	430473297600S1
NBU 285				430473298400S1
NBU 286	3-10-22 SENW	UTU01191	891008900A	430473298500S1
NBU 287	3-10-22 NESE	UT001191A	891008900A	
NBU 288	3-10-22 NWSW	UTU01191	891008900A	430473298600S1
NBU 289	3-10-22 SESW	UTU01191	891008900A	430473291000\$1
NBU 290	3-10-22 SWSE	UTU01191A	891008900A	430473298700S1
NBU 291	9-10-22 NENE	UTU01196D	891008900A	430473291100S1
NBU 292	9-10-22 SWNE	UTU1196D	891008900A	430473347400S1
NBU 293	10-10-22 SENE	UTU025187	891008900A	430473318200S1
NBU 294X	22-9-20 NENW	UTU0577B	891008900A	430473346500S1
NBU 295	12-10-20 SWSW	UTU4478	891008900A	430473293900S1
NBU 296	24-10-20 NWNE	UTU4485	891008900A	430473288600S1
NBU 297	11-9-21 SWNW	UTU0141315	891008900A	430473304000S1
NBU 298	15-9-21 NESW	UTU01188	891008900A	430473304100S1
NBU 299	16-9-21 SWNE	ML3282	891008900A	430473301200S1
NBU 300	21-9-21 NWNW	UTU0576	891008900A	430473302300S1
NBU 301	25-9-21 NWSW	U01194	891008900A	430473285900S1 🗸
NBU 302	26-9-21 SWNW	U01194	891008900A	430473287700S1
NBU 303	26-9-21 SESE	ML22934	891008900A	430473287800S1 ✓
	27-9-21 SESE	U01194A	891008900A	430473287900S1 🗸
NBU 304	27-9-21 SWSE	U01194A	891008900A	430473288000S1 🗸
NBU 305		U01194A	891008900A	430473286000S1
NBU 306	27-9-21 NWNW		891008900A	430473280000S1
NBU 307	28-9-21 NWNE	U05676	891008900A	430473314300S1
NBU 308	28-9-21 SENW	U05676		
NBU 309	30-9-21 NENE	UTU0581	891008900A	430473301000S1 430473288200S1 ✓
NBU 310	35-9-21 NENW	U01194	891008900A	
NBU 311	4-10-22 NESE	UTU01191	891008900A	430473283700\$1
NBU 312-E2	2-9-21 SWSE	UTU21510	891008900A	430473228800S1 🗸
NBU 313	4-10-22 NENW	UTU01191A	891008900A	430473283800S1
NBU 315	11-9-21 SENE	UTU0141317	891008900A	430473387900S1
NBU 316	11-9-21 SWNE	UTU0141317	891008900A	430473441300S1
NBU 317	13-9-21 NENE	U-01193	891008900A	430473392100S1
NBU 318	13-9-21 SWNE	UTU01193	891008900A	430473388000S1
NBU 320	25-9-21 NWNW	U01189	891008900A	430473320100S1
NBU 321	26-9-21 SWSW	U01194	891008900A	430473320200S1 🗸
NBU 322	34-9-21 SESW	U01994	891008900A	430473320300S1 🗸
NBU 323	30-9-22 NENE	U-463	891008900A	430473405000S1
NBU 326	31-9-22 NESW	ML22935A	891008900A	430473320400S1 🗸
NBU 327	33-9-22 SWSE	UTU01191	891008900A	430473373500S1
NBU 329	1-10-21 NESW	UTU02842B	891008900A	430473322700S1
NBU 330	3-10-21 NENE	UTU0149078	891008900A	430473322800S1
NBU 331	3-10-21 NWNE	UTU0149078	891008900A	430473322900S1
1450 001	<del>-</del>			

Westport Project Ed		s Worksh	eet :	,								, , ,					
instructions:		rill in blue to	o woled below o	nd graph vent accl	ed autor dental al	natically teration	at the b of the for	ottom o mulas. :	of the p See JTC	age. This C for cha	s sheet						
		OPX enten	ed as an	nual costs	and/or	as unit O	PX costs	for \$/BF	and \$/	MCF			_				١
Project Name		Condense											J				
is if	nis job a well	pult or prod		g job ??? SEFORE	N	(Y or ]	N) AFTER			FERENCI	E						
Į į	Gross Oil Rev	/enue		\$/Year \$1,088		-\$	/Year \$1,099			\$/Year \$1							
	Gross Gas Re NGL Revenu			\$0 \$0	_		\$0 \$0			\$ \$	0						
	PULING UNIT WIRELINE SER				7			1		\$							1
	SUBSURF EQU	JIP REPAIRS			4						0						
	CONTRACT	LABOR		\$0	4		\$200	1	F	\$20							
	CONTR SERV LEASE FUEL O	GAS.		\$0			\$0	•		\$	Ω.						
	UTILITIES - ÉLI CHEMICAL T			\$0	2		\$0	1	E	3	<u> </u>						
i	MATERIAL &			\$0	7		\$150	] "		\$15 \$	0						-
	ADMINISTRA GAS PLANT	TIVE COSTS	<u> </u>		7			}	F		8 8						
 	GASTUANI	Totals		\$4	5		\$350			\$35	O Ir	creased	OPX	Per Ye	96		- [
	Investment					Oll Pi		5 23.	<b>50  </b> \$/8	10							
	<b>.</b>	Cap/E		Cost, \$	<b>5</b> 7	Gas	Price		10 \$/\		,						
	Capital \$ Expense \$	820/830/ 830/8		\$1,200 \$4	5	OPX.		\$ 2.	00 \$/B	SF.	,						١
	Total \$		L	\$1,20	의	OPX.	/MCF	\$ 0.	62 <b>\$</b> /A	MCF							
	Productio	n & OPX D		fore		Affe	r		DIII	ference							ı
	Oil Product		F		2 BOPD MCFPD			BOPD MCFPD	F	0.00	0 M						
	Wir Produc	tion			8WPD			BWPD	F		O BW						
	Fuel Gas Bu				HP MCFPD			HP MCFPC	Ŀ			CFPD					
ľ																	_
	Project Life		Life =		0 Years			1		viation:			4		- 1		
		(L	ife no lor	nger than	20 years	)		Payor	# <b>-</b>	\$um(O		i invesin ncremen		nue)	'		
	Internat Ra After Tax	te of Return: II		#DIV/OI	3			Payor See g	ut occu raph b	ırs when elow, no	total A	AT cashfil ars when	ow equa	als inve v reaci	stment hes zero	<b>-</b>	
	AT Cum Co			(\$2.91	7) (Disco	unted 6	10%)	Payor	_	NEVER		Years or		ALUÉI	_		
		Cashflow =		(42,71	<u>-//</u> (Disc.			1 -/-									$\dashv$
	Gross Rese Oli Reserve	16 =			6 80												
	Gas Reserv	res = Reserves =			0 MCF 38 MCFE												
Notes/Assu	umpilons:													4			
	An gyerga	e NEU well I on the tan	c. The inc	0.192 Bc reased D	<u>ed with n</u> roduction	o tank r n does n	of payou	the pro	ive co	t or the	estima estima	ted annu	al main	tenano	e cost		
				Proje	et: Cond	lensate :	Shrinkage	Econo	mics								
	<b>\$0</b> -	·!			<del>  </del>	+-	<del>+ +</del>	- +	<del></del>	+	<del>!</del>	<del>: :</del>	- :	-		<del>!</del>	1
	(\$500) -		<u> </u>		<u> </u>						ļ	ļļ.					
	3										ļ	ļļ.					
	(\$1,000) -																
	(\$1,000) - (\$1,500) - (\$1,500) - (\$2,000) -		1		<del></del>												
	(\$2,000) ·				-	-	1					†					
	(\$2,500)	ļ	ļļ.		ļ			-			ļ	-					
	<b>∢</b> (\$3,000) -	<b> </b>			. <b>.</b>	<del>.</del>					ļ				-		1
	(\$3,500)										<u> </u>					<u>.i</u>	ل
	(40,000)	_				•		10	11	12	13	14 15	16	17	18	19	20

Project Year

## Westport Oil and Gas, Inc. NBU/Ouray Field

RFL 2003-022

## **COMPARISON OF FLASH BACK PRESSURES**

Calculated by Characterized Equation-of-State

Flash Conditions		Gas/Oil Ratio (scf/STbbl)	Specific Gravity of Flashed Gas	Separator Volume Factor	Separator Volume Percent	
peig	•F	(A)	( Air=1.000 )	(B)	(C)	
Calculated	et Labora	tory Flash Cond	ltion <b>s</b>			
80	70	•		1.019		
0	122	30.4	0.993	1.033	101.37%	
0 - 4-	60	0.0		1.000	98.14%	
Calculated	Fiash witi	h Backpressure	using Tuned EO	s		
80	70			1.015		
6.0 oz	65	24.6	0.777	1.003	98.82%	
0	60	0.0		1.000	98.52%	
80	70			1.015		
4.0 oz	65	24.7	0.778	1.003	98.82%	
0	60	0.0		1.000	98.52%	
80	70			1.015		
2.0 oz	65	24.7	0.779	1.003	98.82%	
0	60	0.0		1.000	98.52%	
80	70			1.015		
0	65	24.8	0.780	1.003	98.82%	
0	60	0.0	***	1.000	98.52%	

Note: Bubblepoint of sample in original sample container was 80 psig at 70° F with 1 cc water

<sup>(</sup>A) Cubic Feet of gas at 14.696 paia and 60 °F per Barrel of Stock Tank Oil at 60 °F.

<sup>(</sup>B) Barrels of oil at indicated pressure and temperature per Barrel of Stock Tank Oil at 60 °F.

<sup>(</sup>C) Oil volume at indicated pressure and temperature as a percentage of original saturated oil volume.

## Division of Oil, Gas and Mining OPERATOR CHANGE WORKSHEET

ROUTING
1. DJJ
2 CDW

## X Change of Operator (Well Sold)

Operator Name Change/Merger

The operator of the well(s) listed below has changed, effective	1/6/2006					
FROM: (Old Operator):	TO: ( New Operator):					
N2115-Westport Oil & Gas Co., LP	N2995-Kerr-M		Gas Onsho	re, LP		
1368 South 1200 East	1368 S	outh 1200	East			
Vernal, UT 84078	Vernal, UT 84078					
Phone: 1-(435) 781-7024		Phone: 1-(435)	781-7024			
CA No.		Unit:	N	ATURAL I	BUTTES	UNIT
WELL NAME SEC T	WN RNG	API NO	ENTITY	LEASE	WELL	WELL
	٠.		NO	TYPE	TYPE	STATUS
OPERATOR CHANGES DOCUMENTATION	N					
Enter date after each listed item is completed						
1. (R649-8-10) Sundry or legal documentation was received	ed from the	FORMER ope	erator on:	5/10/2006	5	
2. (R649-8-10) Sundry or legal documentation was received	ed from the	NEW operator	on:	5/10/2006	5	
3. The new company was checked on the <b>Department of</b>	Commerce	, Division of C	orporation	s Database	on:	3/7/2006
4a. Is the new operator registered in the State of Utah:		Business Numl	-	1355743-01		
4b. If <b>NO</b> , the operator was contacted contacted on:		,			_	
5a. (R649-9-2)Waste Management Plan has been received o	n:	IN PLACE				
5b. Inspections of LA PA state/fee well sites complete on:		n/a	3 LA wells	s & all PA v	vells tran	sferred
5c. Reports current for Production/Disposition & Sundries	o <b>n</b> :	ok	•			
6. Federal and Indian Lease Wells: The BLM at	nd or the E	IA has appro	ved the n	nerger, na	ne chan	ge,
or operator change for all wells listed on Federal or Ind-	ian leases o	n:	BLM	3/27/2006	BIA	not yet
7. Federal and Indian Units:						
The BLM or BIA has approved the successor of unit of	operator for	wells listed on		3/27/2006		
8. Federal and Indian Communization Agree	ments ("	CA"):				
The BLM or BIA has approved the operator for all we				n/a		,
9. Underground Injection Control ("UIC")		vision has appro		-	sfer of A	uthority to
Inject, for the enhanced/secondary recovery unit/project	et for the wa	ter disposal we	ll(s) listed o	n:		
DATA ENTRY:						
1. Changes entered in the Oil and Gas Database on:		5/15/2006	_			
2. Changes have been entered on the Monthly Operator	Change Sp			5/15/2006	_	
3. Bond information entered in RBDMS on:		5/15/2006	-			
<ul><li>4. Fee/State wells attached to bond in RBDMS on:</li><li>5. Injection Projects to new operator in RBDMS on:</li></ul>		5/16/2006	-			
<ul><li>5. Injection Projects to new operator in RBDMS on:</li><li>6. Receipt of Acceptance of Drilling Procedures for APD/</li></ul>	New on:		n/a	Name Char	nge Only	
BOND VERIFICATION:	TYCW OII.		11/4	TVallic Cha	ige Omy	
Federal well(s) covered by Bond Number:		CO1203				
<ol> <li>Indian well(s) covered by Bond Number:</li> </ol>		RLB0005239	-			
3. (R649-3-1) The <b>NEW</b> operator of any fee well(s) listed	covered by		-	RLB000523	6	
a. The <b>FORMER</b> operator has requested a release of liability	•		n/a	rider adde		
The Division sent response by letter on:	ny nom me	ii bond on.	II/a	_iluei auue	u KWG	
LEASE INTEREST OWNER NOTIFICATION	N:		-			
4. (R649-2-10) The <b>FORMER</b> operator of the fee wells have		acted and infor	ned by a let	ter from the	Division	
of their responsibility to notify all interest owners of this			5/16/2006		21,101011	
COMMENTS:						

Form 3 160-5 (August 1999)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires Jnovember 30, 2000

5.	Lease	Serial	No.

SUNDRY Do not use this abandoned well.	MULTIPLE LEASES  6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPI	LICATE – Other instr	uctions on reverse sid	7. If Unit or CA/Agreement, Name and/or No.	
I. Type of Well				
Oil Well X Gas Well	☐ Other		8. Well Name and No.	
2. Name of Operator			MUTIPLE WELLS	
KERR-McGEE OIL & GAS	ONSHORE LP		9. API Well No.	
3a. Address		3b. Phone No. (include area	code)	
1368 SOUTH 1200 EAST VERNAL, UT 84078 (435) 781-7024			10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec.	, T., R., M., or Survey Descripe			
SEE ATTACHED			11. County or Parish, State UINTAH COUNTY, UTAH	
12. CHECK AP	PROPRIATE BOX(ES) TO	INDICATE NATURE OF N	OTICE, REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Acidize Alter Casing		Production (Start/Resume) Water Shut-Off	
Subsequent Report	Casing Repair Change Plans	New Construction	Recomplete	
Final Abandonment Notice	Convert to Injection	Plug Back	emporarily Abandon OPERATOR  Vater Disposal	
13. Describe Proposed or Completed Op  If the proposal is to deepen direction	erations (clearly state all pertiner nally or recomplete horizontally,	nt details, including estimated startingive subsurface locations and measu	g date of any proposed work and approximate duration thereof. red and true vertical depths of all pertinent markers and zones.	

If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.

PLEASE BE ADVISED THAT KERR-McGEE OIL & GAS ONSHORE LP, IS CONSIDERED TO BE THE OPERATOR OF THE ATTACHED WELL LOCATIONS. EFFECTIVE JANUARY 6, 2006.

KERR-McGEE OIL & GAS ONSHORE LP, IS DESPONSIBLE LINDER TERMS AND CONSIDERED.

RECEIVED

KERR-McGEE OIL & GAS ONSHORE LP, IS RESPONSIBLE UNDER TERMS AND CONDITIONS OF THE LEASE(S) FOR THE OPERATIONS CONDUCTED UPON LEASE LANDS. BOND COVERAGE

BIM BOND = CDI202

MAY 1 0 2006

IS PROVIDED BY STATE OF UTAH NATIONWIDE BOND NO. RLB0005237.

DIV. OF OIL, GAS & MINING

<ol> <li>I hereby certify that the foregoing is true and corn Name (Printed/Typed)</li> <li>FANDY BAYNE</li> </ol>	Title Earlene Ru  DRILLING MANAGER	lene Russell  16 Oil, Gas and Mining  18 Ussell, Engineering Technician
Signature / Sayne	Date <b>May</b> 9, 2006	
	THIS SPACE FOR FEDERAL OR STATE U	JSE
Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this certify that the applicant holds legal or equitable title to those which would entile the applicant to conduct operations thereo	rights in the subject lease	3076

Title 18 U.S.C. Section 1001, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Form 3 160-5 (August 1999)

#### UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB No. 1004-0135 Expires Jnovember 30, 2000

5. Lease Serial No.

## MULTIPLE LEASES

SUNDRY NOTICES AND REPORTS ON WELLS

	Use Form 3160-3 (APD)			6. If Indian, Allottee or Tribe 1	√arne		
SUBMIT IN TRIPL	ICATE – Other instru	ctions on rev	erse side	7. If Unit or CA/Agreement, N	ame and/or No.		
I. Type of Well							
Oil Well X Gas Well	Other			8. Well Name and No.			
2. Name of Operator				MUTIPLE WELLS			
WESTPORT OIL & GAS CO	MPANY L.P.			9. API Well No.			
3a. Address		3b. Phone No.	include area code)				
1368 SOUTH 1200 EAST V		(435) 781-70	24	10. Field and Pool, or Explorato	ry Area		
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Description	n)					
055 47740450				11. County or Parish, State			
SEE ATTACHED				UINTAH COUNTY, UTA	UINTAH COUNTY, UTAH		
12. CHECK APP	ROPRIATE BOX(ES) TO I	NDICATE NAT	URE OF NOTICE	E, REPORT, OR OTHER DATA			
TYPE OF SUBMISSION			TYPE OF ACT	ION			
Notice of Intent	Acidize	Deepen	Produc	tion (Start/Resume)   Water Shut-	Off		
_	Alter Casing	Fracture Trea	_				
Subsequent Report	Casing Repair	New Construe		plete 👿 Other CHA	•		
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Aba	= '	rarily Abandon OPERATO	R		
13. Describe Proposed or Completed Open	· – ·	Plug Back		Disposal			
rottowing completion of the involved	perations. If the operation result bandonment Notices shall be filed at inspection.  DO6, WESTPORT OIL & THE ATTACHED WELL	is in a multiple com I only after all requ GGAS COMPA LOCATIONS	pletion or recompleti rements, including r ANY L.P., HAS TO KERR-Mc	GEE OIL & GAS	1 L. CI_1		
	APPR	OVED 3	5/6/06	RECEI	√ED		
	$\mathcal{L}a$	rlove Ri	issell		-		
	Division	of Oil, Gas an	d Mining	MAY 1 0	2006		
	Dariene F	cussell, Engine	ering Technic	lan DIV OF OU OAR	0.111111		
14. I hereby certify that the foregoing	s is true and correct			DIV OF OIL GAS	* WINING		
Name (Printed/Typed)		Title					
BRAD LANEY Signature	<del></del>		ING SPECIAL	IST			
orginature .		Date May 9, 2006	3				
	THIS SPACE	FOR FEDERAL					
Approved by		Title		Date			
Olack January				5-9-06			
Conditions of approval, if any, are attacked certify that the applicant holds legated equit which would entitle the applicant to conduct	able title to those rights in the subje	arrant or Office					
Title 18 U.S.C. Section 1001, make false, fictitious or fraudulent statemer	it a crime for any person know	vingly and willfull matter within its ju	y to make to any durisdiction.	lepartment or agency of the United S	tates any		



## **United States Department of the Interior**

BUREAU OF LAND MANAGEMENT Colorado State Office 2850 Youngfield Street Lakewood, Colorado 80215-7076

IN REPLY REFER TO:

CO922 (MM) 3106 COC017387 et. al.

March 23, 2006

#### NOTICE

Kerr-McGee Oil & Gas Onshore L.P. 1999 Broadway, Suite 3700 Denver, CO 80202

Oil & Gas

#### Merger/Name Change - Recognized

On February 28, 2006 this office received acceptable evidence of the following mergers and name conversion:

Kerr-McGee Oil & Gas Onshore L.P., a Delaware Limited Partnership, and Kerr-McGee Oil & Gas Onshore LLC, a Delaware Limited Partnership merger with and into Westport Oil and Gas Company L.P., a Delaware Limited Partnership, and subsequent Westport Oil & Gas Company L.P. name conversion to Kerr-McGee Oil & Gas Onshore L.P.

For our purposes the merger and name conversion was effective January 4, 2006, the date the Secretary of State of Delaware authenticated the mergers and name conversion.

Kerr-McGee Oil & Gas Onshore L.P. provided a list of oil and gas leases held by the merging parties with the request that the Bureau of Land Management change all their lease records from the named entities to the new entity, Kerr-McGee Oil & Gas Onshore L.P. In response to this request each state is asked to retrieve their own list of leases in the names of these entities from the Bureau of Land Management's (BLM) automated LR2000 data base.

The oil and gas lease files identified on the list provided by Kerr-McGee Oil & Gas Onshore L.P. have been updated as to the merger and name conversion. We have not abstracted the lease files to determine if the entities affected by the acceptance of these documents holds an interest in the lease, nor have we attempt to identify leases where the entity is the operator on the ground that maintains vested record title or operating rights interests. If additional documentation, for change of operator, is required you will be contacted directly by the appropriate Field Office. The Mineral Management Services (MMS) and other applicable BLM offices were notified of the merger with a copy of this notice

Please contact this office if you identify additional leases where the merging party maintains an interest, under our jurisdiction, and we will document the case files with a copy of this notice. If the leases are under the jurisdiction of another State Office that information will be forwarded to them for their action.

Three riders accompanied the merger/name conversion documents which will add Kerr-McGee Oil and Gas Onshore LLC as a principal to the 3 Kerr-McGee bonds maintained by the Wyoming State Office. These riders will be forward to them for their acceptance.

The Nationwide Oil & Gas Continental Casualty Company Bond #158626364 (BLM Bond #CO1203), maintained by the Colorado State Office, will remain in full force and effect until an assumption rider is accepted by the Wyoming State Office that conditions their Nationwide Safeco bond to accept all outstanding liability on the oil and gas leases attached to the Colorado bond.

If you have questions about this action you may call me at 303,239,3768.

/s/Martha L. Maxwell Martha L. Maxwell Land Law Examiner Fluid Minerals Adjudication

#### Attachment:

List of OG Leases to each of the following offices:
MMS MRM, MS 357B-1
WY, UT, NM/OK/TX, MT/ND, WY State Offices
CO Field Offices
Wyoming State Office
Rider #1 to Bond WY2357

Rider #1 to Bond WY2357 Rider #2 to Bond WY1865 Rider #3 to Bond WY1127



## United States Department of the Interior



BUREAU OF LAND MANAGEMENT Utah State Office P.O. Box 45155 Salt Lake City, UT 84145-0155 http://www.blm.gov

IN REPLY REFER TO: 3106 (UT-922)

March 27, 2006

#### Memorandum

To:

Vernal Field Office

From:

Chief, Branch of Fluid Minerals

Subject:

Merger Approval

Attached is an approved copy of the merger recognized by the Bureau of Land Management, Colorado State Office. We have updated our records to reflect the merger from Westport Oil and Gas Company L.P. into Kerr-McGee Onshore Oil and Gas Company. The merger was approved effective January 4, 2006.

Chief, Branch of Fluid Minerals

#### Enclosure

Approval letter from BLM COSO (2 pp)

CC:

MMS, Reference Data Branch, James Sykes, PO Box 25165, Denver CO 80225

State of Utah, DOGM, Attn: Earlene Russell, PO Box 145801, SLC UT 84114

Teresa Thompson

Joe Incardine

Connie Seare

Dave Mascarenas

Susan Bauman

MAR 2 8 2006

TOLOFOL, CAO 2 LINE D